



Federal Aviation  
Administration

TM

# Aeronautical Information Services Aeronautical Chart User's Guide

12<sup>th</sup> Edition




**Aeronautical Information Services (AIS)**  
**For More Information on FAA Aeronautical Charts:**

**[aeronav.faa.gov](http://aeronav.faa.gov)**

**Purchase FAA Aeronautical Charts and Publications from authorized  
Aeronautical Chart Agents located at or near many civil airports.**

**Locate one in your area at:**

**[aeronav.faa.gov](http://aeronav.faa.gov)**





# FAA Aeronautical Chart User's Guide

12<sup>th</sup> EDITION OCTOBER 2013

INTRODUCTION.....	5
KEEP YOUR CHARTS CURRENT.....	5
REPORTING CHART DISCREPANCIES.....	5
SECTION 1: VISUAL FLIGHT RULES (VFR) CHARTS	
EXPLANATION OF VFR TERMS AND SYMBOLS.....	6
WATER FEATURES (HYDROGRAPHY).....	6
LAND FEATURES (TERRAIN) AND OBSTRUCTIONS.....	6
RADIO AIDS TO NAVIGATION.....	8
AIRPORTS.....	8
CONTROLLED AIRSPACE.....	9
UNCONTROLLED AIRSPACE.....	10
SPECIAL USE AIRSPACE.....	10
OTHER AIRSPACE AREAS.....	10
TERMINAL AREA CHART (TAC) COVERAGE.....	11
INSET COVERAGE.....	11
CHART TABULATIONS.....	12
VFR AERONAUTICAL CHART SYMBOLS.....	14
AIRPORTS.....	15
RADIO AIDS TO NAVIGATION.....	17
AIRSPACE INFORMATION.....	19
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	25
CHART LIMITS.....	27
RAILROADS.....	28
ROADS.....	28
POPULATED PLACES.....	29
BOUNDARIES.....	29
MISCELLANEOUS CULTURAL FEATURES.....	30
SHORELINES.....	31
LAKES.....	31
RESERVOIRS.....	31
STREAMS.....	31
MISCELLANEOUS HYDROGRAPHIC FEATURES.....	32
CONTOURS.....	35
ELEVATIONS.....	35
UNRELIABLE RELIEF.....	35
SHADED RELIEF.....	36
AREA RELIEF FEATURES.....	36
MISCELLANEOUS RELIEF FEATURES.....	36
HELICOPTER ROUTE CHARTS.....	37
AIRPORTS.....	38
RADIO AIDS TO NAVIGATION.....	38
AIRSPACE INFORMATION.....	39
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	42
CULTURE.....	43
HYDROGRAPHY.....	43
RELIEF.....	43
VFR FLYWAY PLANNING CHARTS.....	44
AIRPORTS.....	45
RADIO AIDS TO NAVIGATION.....	45





AIRSPACE INFORMATION.....	46
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	48
CULTURE.....	49
HYDROGRAPHY.....	49
RELIEF.....	49
<b>AIRSPACE CLASSES.....</b>	<b>50</b>
<b>SECTION 2: INSTRUMENT FLIGHT RULES (IFR) ENROUTE CHARTS</b>	
<b>EXPLANATION OF IFR ENROUTE TERMS AND SYMBOLS.....</b>	<b>52</b>
AIRPORTS.....	53
RADIO AIDS TO NAVIGATION (NAVAIDs).....	54
CONTROLLED AIRSPACE.....	54
SPECIAL USE AIRSPACE.....	55
OTHER AIRSPACE.....	55
INSTRUMENT AIRWAYS.....	55
VOR LF/MF AIRWAY SYSTEM (LOW ALTITUDE ENROUTE CHARTS).....	55
AIRWAY/ROUTE DATA.....	55
AREA NAVIGATION (RNAV) "T" ROUTE SYSTEM.....	56
OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDE (OROCA).....	56
MILITARY TRAINING ROUTES (MTRs).....	56
JET ROUTE SYSTEM (HIGH ALTITUDE ENROUTE CHARTS).....	57
RNAV "Q" ROUTE SYSTEM (HIGH ALTITUDE ENROUTE CHARTS).....	57
AREA NAVIGATION (RNAV) "Q" ROUTE SYSTEM (HIGH ALTITUDE CHARTS).....	57
TERRAIN CONTOURS ON AREA CHARTS.....	57
<b>IFR AERONAUTICAL CHART SYMBOLS.....</b>	<b>58</b>
IFR ENROUTE LOW/HIGH ALTITUDE CHARTS.....	59
AIRPORTS.....	59
RADIO AIDS TO NAVIGATION.....	60
AIRSPACE INFORMATION.....	61
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	66
CULTURE.....	67
HYDROGRAPHY.....	67
TOPOGRAPHY.....	67
OCEANIC ROUTE PLANNING CHARTS.....	68
AIRPORTS.....	68
RADIO AIDS TO NAVIGATION.....	68
AIRSPACE INFORMATION.....	68
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	69
CULTURAL BOUNDARIES.....	70
HYDROGRAPHY.....	70
<b>SECTION 3: TERMINAL PROCEDURES PUBLICATION (TPP)</b>	
<b>EXPLANATION OF TPP TERMS AND SYMBOLS.....</b>	<b>72</b>
PILOT BRIEFING INFORMATION.....	72
PLANVIEW.....	73
MISSED APPROACH ICONS.....	73
IFR LANDING MINIMA.....	73
TERMINAL ARRIVAL AREAS (TAAs).....	74
INSTRUMENT APPROACH CHART FORMAT.....	75
<b>TERMINAL PROCEDURES PUBLICATION SYMBOLS.....</b>	<b>76</b>
STANDARD TERMINAL ARRIVAL (STAR) CHARTS.....	77
DEPARTURE PROCEDURE (DP) CHARTS.....	77
APPROACH LIGHTING SYSTEM.....	78
AIRPORT DIAGRAM/SKETCH.....	81
INSTRUMENT APPROACH PROCEDURES PLANVIEW.....	83
INSTRUMENT APPROACH PROCEDURES PROFILE VIEW.....	85







## INTRODUCTION

This Chart User's Guide is an introduction to the Federal Aviation Administration's (FAA) aeronautical charts and publications. It is useful to new pilots as a learning aid, and to experienced pilots as a quick reference guide.

The FAA publishes charts for each stage of Visual Flight Rules (VFR) and Instrument Flight Rules (IFR) air navigation including training, planning, and departures, enroute (for low and high altitudes), approaches, and taxiing charts. For Procurement, contact an Authorized FAA Chart Sales Agent. Visit our website at <http://aeronav.faa.gov> and click on "Chart Agent Locator." For digital products, visit <http://faacharts.faa.gov>.

The FAA Aeronautical Information Manual (AIM) Pilot/Controller Glossary defines in detail, all terms and abbreviations used throughout this publication. Unless otherwise indicated, miles are nautical miles (NM), altitudes indicate feet above Mean Sea Level (MSL), and times used are Coordinated Universal Time (UTC).

The Notices to Airmen Publication (NOTAM) includes current Flight Data Center (FDC) NOTAMs. NOTAMs alert pilots of new regulatory requirements and reflect changes to Standard Instrument Approach Procedures (SIAPs), flight restrictions, and aeronautical chart revisions. This publication is prepared every 28 days by the FAA, and is available by subscription from the Government Printing Office.

In addition to NOTAMs, the Airport/Facility Directory (A/FD) and the Special Notices page of the Aeronautical Information Services website are also useful to pilots.

### KEEP YOUR CHARTS CURRENT

Aeronautical information changes rapidly, so it is important that pilots check the effective dates on each aeronautical chart and publication. To avoid danger, it is important to always use current editions and discard obsolete charts and publications.

To confirm that a chart or publication is current, refer to the next scheduled edition date printed on the cover. Pilots should also check Aeronautical Chart Bulletins in the A/FD, the Aeronautical Information Services website ([aeronav.faa.gov](http://aeronav.faa.gov)) and NOTAMs for important updates between chart and publication cycles that are essential for safe flight.

All information in this guide is effective through September 2013. All graphics used in this guide are for educational purposes. Please do not use them for flight navigation.

### REPORTING CHART DISCREPANCIES

Your experience as a pilot is valuable and your feedback is important. We make every effort to display accurate information on all FAA charts and publications, so we appreciate your input. Please notify us concerning any requests for changes, or potential discrepancies you see while using our charts and related products.

**FAA, Aeronautical Information Services  
Customer Operations Team  
1305 East-West Highway  
SSMC-4, Suite 4400  
Silver Spring, MD 20910-3281**

**Telephone Toll-Free 1-800-638-8972  
E-mail: [9-AMC-Aerochart@faa.gov](mailto:9-AMC-Aerochart@faa.gov)**



## VFR AERONAUTICAL CHARTS

### EXPLANATION OF VFR TERMS AND SYMBOLS

This chapter covers the Sectional Aeronautical Chart (Sectional). These charts include the most current data at a scale of (1:500,000) which is large enough to be read easily by pilots flying by sight under Visual Flight Rules. Sectionals are named after a major city within its area of coverage.

The chart legend includes aeronautical symbols and information about drainage, terrain, the contour of the land, and elevation. You can learn to identify aeronautical, topographical, and obstruction symbols (such as radio and television towers) by using the legend.


A brief description next to a small black square indicates the exact location for many of the landmarks easily recognized from the air, such as stadiums, pumping stations, refineries, etc. A small open circle indicates an Oil Well. Small black circles with a label show the location of water, oil and gas tanks. The scale for some items may be increased to make them easier to read on the chart.

AeroNav Products' charts are prepared in accordance with specifications of the Interagency Air Cartographic Committee (IACC) and are approved by representatives of the Federal Aviation Administration (FAA) and the Department of Defense (DoD).

### WATER FEATURES (HYDROGRAPHY)

Water features are depicted using two tones of blue, and are considered either "Open Water" or "Inland Water." "Open Water," a lighter blue tone, shows the shoreline limitations of all coastal water features at the average (mean) high water levels for oceans and seas. Light blue also represents the connecting waters like bays, gulfs, sounds, fjords, and large estuaries.

Exceptionally large lakes like the Great Lakes, Great Salt Lake, and Lake Okeechobee, etc., are considered Open Water features. The Open Water tone extends inland as far as necessary to adjoin the darker blue "Inland Water" tones. All other bodies of water are marked as "Inland Water" in the darker blue tone.



### LAND FEATURES (TERRAIN) AND OBSTRUCTIONS

The elevation and configuration of the Earth's surface is important to pilots. Our Aeronautical Information Specialists are devoted to showing the contour of the earth and any obstructions clearly and accurately on our charts. We use five different techniques: contour lines, shaded relief, color tints, obstruction symbols, and Maximum Elevation Figures (MEF).


1. Contour lines join points of equal elevation. On Sectionals, basic contours



are spaced at 500' intervals. Intermediate contours are typically at 250' intervals in moderately level or gently rolling areas. Auxiliary contours at 50', 100', 125', or 150' intervals occasionally show smaller relief features in areas of relatively low relief. The pattern of these lines and their spacing gives the pilot a visual concept of the terrain. Widely spaced contours represent gentle slopes, while closely spaced contours represent steep slopes.



2. Shaded relief shows how terrain may appear from the air. Shadows are shown as if light is coming from the northwest, because studies show that our visual perception has been conditioned to this view.
3. Different color tints show bands of elevation relative to sea level. These colors range from light green for the lower elevations, to dark brown for the higher elevations.
4. Obstruction symbols show man made vertical features that could affect safe navigation. FAA's Aeronautical Information Management (AIM) maintains a database of over 1,200,000 obstacles in the United States, Canada, the Caribbean, Mexico and U.S. Pacific Island Territories. Aeronautical Specialists evaluate each obstacle based on charting specifications before adding it to a visual chart. When a Specialist is not able to verify the position or elevation of an obstacle, it is marked UC, meaning it is "under construction" or being reported, but has not been verified.



The FAA uses a Digital Obstacle File (DOF) to collect and disseminate data. Because land and obstructions frequently change, the source data on obstructions and terrain is occasionally incomplete or not accurate enough for use in aeronautical publications. For example, when the FAA receives notification about an obstruction, and there is insufficient detail to determine its position and elevation, the FAA Flight Edit Program conducts an investigation.

The Flight Edit crew visually verifies the cultural, topographic, and obstacle data. Charts are generally flight-checked every four years. This review includes checking for any obstruction that has been recently built, altered, or dismantled without proper notification.

Obstacles less than  
1000' AGL.

Obstacles greater than  
1000' AGL.


Sectional Charts and Terminal Area Charts (TACs) typically show manmade obstacles extending more than 200' Above





Ground Level (AGL), unless they appear in yellow city tint. Features considered to be hazardous obstacles to low-level flight are; smokestacks, tanks, factories, lookout towers, and antennas, etc. On World Aeronautical Charts (WACs) only those obstacles at 500' AGL and higher are charted.


Manmade features used by FAA Air Traffic Control as checkpoints use a graphic symbol shown in black with the required elevation data in blue. The elevation of the top of the obstacle above Mean Sea Level (MSL) and the height of the structure (AGL) is also indicated (when known or can be reliably determined by a Specialist). The AGL height is in parentheses below the MSL elevation. In extremely congested areas, the FAA typically omits the AGL values to avoid confusion.




Whenever possible, the FAA depicts specific obstacles on charts. However, in high-density areas like city complexes, only the highest obstacle is represented on the chart using the group obstacle symbol to maximize legibility.



Obstacles under construction are indicated by placing the letters UC next to the obstacle type.




Obstacles with high-intensity strobe lighting systems may operate part-time or by proximity activation and are shown as follows:



- The Maximum Elevation Figure (MEF) represents the highest elevation within a quadrant, including terrain and other vertical obstacles (towers, trees, etc.). A quadrant on Sectionals is the area bounded by ticked lines dividing each 30 minutes of latitude and each 30 minutes of longitude. MEF figures are rounded up to the nearest 100' value and the last two digits of the number are not shown.

MEFs over land and open water areas are used in areas containing manmade obstacles such as oil rigs.

In the determination of MEFs, the FAA uses extreme care to calculate the values based on the existing elevation data shown on source material. Aeronautical Information Specialists use the following procedure to calculate MEFs:



When a manmade obstacle is more than 200' above the highest terrain within the quadrant:

- Determine the elevation of the top of the obstacle above MSL.
- Add the possible vertical error of the source material to the above figure (100' or 1/2 contour interval when interval on source exceeds 200'. U.S. Geological Survey Quadrangle Maps with contour intervals as small as 10' are normally used).
- Round the resultant figure up to the next higher hundred-foot level.

#### Example:

Elevation of obstacle top (MSL) =	2424
Possible vertical error	+100
	<b>equals 2524</b>
Raise to the following 100' level	2600
Maximum Elevation Figure	<b>26</b>

When a natural terrain feature or natural vertical obstacle (e.g. a tree) is the highest feature within the quadrangle:

- Determine the elevation of the feature.
- Add the possible vertical error of the source to the above figure (100' or 1/2 the contour interval when interval on source exceeds 200').
- Add a 200' allowance for uncharted natural or manmade obstacles. Chart specifications don't require the portrayal of obstacles below minimum height.
- Round the figure up to the next higher hundred-foot level.

#### Example:


Elevation of obstacle top (MSL) =	3450
Possible vertical error	+100
Obstacle Allowance	+200
	<b>equals 3750</b>
Raise to the following 100' level	3800
Maximum Elevation Figure	<b>38</b>

Pilots should be aware that while the MEF is based on the best information available to the Specialist, the figures are not verified by field surveys. Also, users should consult the Aeronautical Chart Bulletin in the A/FD or AeroNav Products website to ensure that your chart has the latest MEF data available.




## RADIO AIDS TO NAVIGATION

On VFR Charts, information about radio aids to navigation (NAVAID) is boxed, as illustrated. Duplication of data is avoided. When two or more radio aids in a general area have the same name with different frequencies, Tactical Air Navigation (TACAN) channel numbers, or identification letters, and no misinterpretation can result, the name of the radio aid may be indicated only once within the identification box. Very High Frequency/Ultra High Frequency (VHF/UHF) Navigation Aid (NAVAID) names and identification boxes (shown in blue) take precedence. Only those items that differ (e.g., frequency, Morse Code) are repeated in the box in the appropriate color. The choice of separate or combined boxes is made in each case on the basis of economy of space and clear identification of the radio aids.



A NAVAID that is physically located on an airport may not always be represented as a typical NAVAID symbol. A small open circle indicates the NAVAID location when collocated with an airport icon. The type of NAVAID will be identified by: “VOR,” (VHF Omni-Directional Range) “VORTAC” (VOR Tactical Aircraft Control) or “VOR-DME,” (VOR-Distance Measuring Equipment) positioned on and breaking the top line of the NAVAID box.



## AIRPORTS

Airports in the following categories are charted as indicated (additional symbols are shown later in this Section).

### Public use airports:

- Hard-surfaced runways greater than 8069' or some multiple runways less than 8069'
- Hard-surfaced runways 1500' to 8069'
- Other than hard-surfaced runways
- Seaplane bases

### Military airports:

- Other than hard-surfaced runways

Hard-surfaced U.S. military runways are depicted like public-use airports. They are identified by abbreviations such as: AAF (Army Air Field), AFB (Air Force Base), MCAS (Marine Corps Air Station), NAS (Naval Air Station), NAF (Naval Air Facility), NAAS (Naval Auxiliary Air Station), etc.

Canadian military airports are identified by the abbreviation DND (Department of National Defense).

### Services available:



Tick marks around the basic airport symbol indicate that fuel is available and the airport is tended during normal working hours (Monday through Friday 10:00 A.M. to 4:00 P.M. local time).

### Other airports with or without services:




Airports are plotted in their true geographic position unless the symbol conflicts with a NAVAID at the same location. In such cases, the airport symbol will be displaced, but the relationship between the airport and the NAVAID will be retained.

Airports are identified by their designated name. Generic parts of long airport names (such as “airport,” “field,” or “municipal”) and the first names of persons are commonly omitted unless they are needed to distinguish one airport from another with a similar name.



The figure at right illustrates the coded data that is provided along with the airport name.

The elevation of an airport is the highest point on the usable portion of the landing areas. Runway length is the length of the longest active runway, including displaced thresholds and excluding overruns. Runway length is shown to the nearest 100', using 70 as the rounding point; a runway 8070' in length is charted as 81, while a runway 8069' in length is charted as 80. If a seaplane base is collocated with an airport, there will be additional seaplane base water information listed for the elevation, lighting and runway.







- FSS** - Flight Service Station on field
- NO SVFR** - Airports where fixed wing special visual flight rules operations are prohibited (shown above airport name) F.A.R. 91
-  - Indicates F.A.R. 93 Special Air Traffic Rules and Airport Traffic Patterns
- (NAM)** - Location Identifier
- (PNAM)** - ICAO Location Indicator
- CT - 118.3** - Control Tower (CT) - primary frequency
- ★ - Star indicates operation part-time. See tower frequencies tabulation for hours of operation
  -  - Follows the Common Traffic Advisory Frequency (CTAF) (Not shown on WAC)
- ATIS 123.8** - Automatic Terminal Information Service
- AFIS 135.2** - Automatic Flight Information Service
- ASOS/AWOS 135.42** - Automated Surface Weather Observing Systems; shown when full-time ATIS is not available. (Not shown on WAC) Some ASOS/AWOS facilities may not be located at airport.
- 897** - Elevation in feet
- L** - Lighting in operation Sunset to Sunrise
  - \***L** - Lighting limitations exist; refer to Airport/Facility Directory.
- 110** - Length of longest runway in hundreds of feet; usable length may be less.
- UNICOM** - Aeronautical advisory station ("U" only on WAC)
- RP 23, 34** - Runways with Right Traffic Patterns (public use) (Not shown on WAC)
- RP\*** - (See Airport/Facility Directory)
- VFR Advsy 125.0** - VFR Advisory Service shown where ATIS is not available and frequency is other than primary CT frequency.
- WX CAM** - Weather Camera (AK)
- AOE** - Airport of Entry

Airports with Control Towers (CT) and their related data are shown in blue. All other airports and their related data are shown in magenta. The **L** symbol indicates that runway lights are on from dusk to dawn. A \***L** indicates that the pilot must consult the Airport/Facility Directory (A/FD) to determine runway lighting limitations, such as: available on request (by radio-call, letter, phone, etc), part-time lighting, or pilot/airport controlled lighting. Lighting codes refer to runway edge lights. The lighted runway may not be the longest runway available, and lights may not be illuminated along the full length of the runway. The A/FD has a detailed description of airport and air navigation lighting aids for each airport. A dash represents no runway edge lights.

The symbol ★ indicates the existence of a rotating or flashing airport beacon operating from dusk to dawn. The Aeronautical Information Manual (AIM) thoroughly explains the types and uses of airport lighting aids.

Right traffic information is shown using the abbreviation 'RP' for right pattern, followed by the appropriate runway number(s) (RP 18). Special conditions or restrictions to the right pattern are indicated by the use of an asterisk (RP\*) to direct the pilot to the Airport/Facility Directory for special instructions and/or restrictions.

An airport with an objectionable airspace will be labeled as such, "OBJECTIONABLE." This airport may adversely affect airspace use. FAA Airports Offices are responsible for airspace determinations and follow FAA Order 7400.2. If an airport owner or chart user wishes to challenge the objectionable status, he or she should contact their FAA Regional Airports Office.

## CONTROLLED AIRSPACE

Controlled airspace consists of those areas where some or all aircraft may be subject to air traffic control, such as: Class A, Class B, Class C, Class D, Class E Surface (SFC) and Class E Airspace.

**Class A Airspace** within the United States extends from 18,000' up to 60,000' MSL. While visual charts do not depict Class A, it is important to note its existence.

**Class B Airspace** is shown in abbreviated form on the World Aeronautical Chart (WAC). The Sectional Aeronautical Chart (Sectional) and Terminal Area Chart (TAC) show Class B in greater detail. The MSL ceiling and floor altitudes of each sector are shown in solid blue figures with the last two zeros omitted. Floors extending "upward from above" a certain altitude are preceded by a (+). Operations at and below these altitudes are outside of Class B Airspace. Radials and arcs used to define Class B are prominently shown on TACs. Detailed rules and requirements associated with the particular Class B are shown. The name by which the Class B is identified is shown as **LAS VEGAS CLASS B** for example.

Class B MSL **90**  
Altitudes **20**

**Class C Airspace** is shown in abbreviated form on WACs. Sectionals and TACs show Class C in greater detail.

The MSL ceiling and floor altitudes of each sector are shown in solid magenta figures with the last two zeros eliminated.

Class C MSL **70**  
Altitudes **15**

The figure at right identifies a sector that extends from the surface to the base of the Class B.

**T**  
**SFC**

Class C airspace is identified by name: **BURBANK CLASS C**.

Separate notes, enclosed in magenta boxes, give the approach control frequencies to be used by arriving VFR aircraft to establish two-way radio communication before entering the Class C (generally within 20 NM):

CTC BURBANK APP WITHIN  
20 NM ON 124.6 395.9

**Class D Airspace** is identified with a blue dashed line. Class D operating less than continuous is indicated by the following note:

See NOTAMS/Directory  
for Class D eff hrs

Ceilings of Class D are shown as follows: **[30]**.

A minus in front of the figure is used to indicate "from surface to, but not including..."

**Class E Surface (SFC) Airspace** is symbolized with a magenta dashed line. Class E (SFC) operating less than continuous is indicated by the following note:

See NOTAMS/Directory  
for Class E (sfc) eff hrs






**Class E Airspace** exists at 1200' AGL unless designated otherwise. The lateral and vertical limits of all Class E, (up to, but not including 18,000') are shown by narrow bands of vignette on Sectionals and TACs.

Controlled airspace floors of 700' above the ground are defined by a magenta vignette; floors other than 700' that laterally abuts uncontrolled airspace (Class G) are defined by a blue vignette; differing floors greater than 700' above the ground are annotated by a symbol and a number indicating the floor.

If the ceiling is less than 18,000' MSL, the value (preceded by the word "ceiling") is shown along the limits of the controlled airspace. These limits are shown with the same symbol indicated above.




## UNCONTROLLED AIRSPACE

**Class G Airspace** within the United States extends up to 14,500' Mean Sea Level. At and above this altitude is Class E, excluding the airspace less than 1500' above the terrain and certain special use airspace areas.


## SPECIAL USE AIRSPACE

**Special Use Airspace (SUA)** confines certain flight activities and restricts entry, or cautions other aircraft operating within specific boundaries. Except for Controlled Firing Areas, SUA areas are depicted on VFR Charts. Controlled Firing Areas are not charted because their activities are suspended immediately when spotter aircraft, radar, or ground lookout positions indicate an aircraft might be approaching the area. Nonparticipating aircraft are not required to change their flight paths. SUA areas are shown in their entirety (within the limits of the chart), even when they overlap, adjoin, or when an area is designated within another area. The areas are identified by type and identifying name/number, and are positioned either within or immediately adjacent to the area.

PROHIBITED, RESTRICTED  
or WARNING AREA



ALERT AREA



MILITARY OPERATIONS  
AREA (MOA)



## OTHER AIRSPACE AREAS

**Mode C Required Airspace** (from the surface to 10,000' MSL) within 30 NM radius of the primary airport(s) for which a Class B is designated, is depicted by a solid magenta line.

MODE C  
30 NM

Mode C is required, but not depicted for operations within and above all Class C up to 10,000' MSL. Enroute Mode C requirements (at and above 10,000' MSL except in airspace at and below 2500' AGL) are not depicted. See FAR 91.215 and the AIM.

**FAR 93** Airports and heliports under Federal Aviation Regulation 93 (FAR 93), (Special Air Traffic Rules and Airport Traffic Patterns), are shown by "boxing" the airport name.



TRUCKEE - TAHOE

**FAR 91** Airports where fixed wing special visual flight rules operations are prohibited (FAR 91) are shown with the type "NO SVFR" above the airport name.

**National Security Areas** indicated with a broken magenta line and **Special Flight Rules Areas (SFRAs)** indicated with the following symbol: , consist of airspace with defined vertical and lateral dimensions established at locations where there is a requirement for increased security and safety of ground facilities. Pilots should avoid flying through these depicted areas. When necessary, flight may be temporarily prohibited.

**The Washington DC Flight Restricted Zone (FRZ)** is related to National Security. It is depicted using the Prohibited/Restricted/Warning Area symbology and is located within the SFRA. It is defined as the airspace within approximately a 13 to 15 NM radius of the DCA VOR-DME. Additional requirements are levied upon aviators requesting access to operate inside the National Capital Region.

**Temporary Flight Restriction (TFR) Areas Relating to National Security** are indicated with a broken blue line . A Temporary Flight Restriction (TFR) is a type of Notice to Airmen (NOTAM). A TFR defines an area where air travel is restricted due to a hazardous condition, a special event, or a general warning for the entire airspace. The text of the actual TFR contains the fine points of the restriction. It is important to note that only TFRs relating to National Security are charted.

**Air Defense Identification Zones (ADIZs)** are symbolized using the ADIZ symbol: . As defined in Code of Federal Regulations 14 (CFR 14) Part 99, an ADIZ is an area in which the ready identification, location, and control of all aircraft is required in the interest of national security. ADIZ boundaries include Alaska, Canada and the Contiguous U.S.


**Terminal Radar Service Areas (TRSAs)** are shown in their entirety, symbolized by a screened black outline of the entire area including the various sectors within the area .





The outer limit of the entire TRSA is a continuous screened black line. The various sectors within the TRSA are symbolized by narrower screened black lines.

Each sector altitude is identified in solid black color by the MSL ceiling and floor values of the respective sector, eliminating the last two zeros. A leader line is used when the altitude values must be positioned outside the respective sectors because of charting space limitations. The TRSA name is shown near the north position of the TRSA as follows: **PALM SPRINGS TRSA**. Associated frequencies are listed in a table on the chart border.

**Military Training Routes (MTRs)** are shown on Sectionals and TACs. They are identified by the route designator: . Route designators are shown in solid black on the route centerline, positioned along the route for continuity. The designator IR or VR is not repeated when two or more routes are established over the same airspace, e.g., IR201-205-227. Routes numbered 001 to 099 are shown as IR1 or VR99, eliminating the initial zeros. Direction of flight along the route is indicated by small arrowheads adjacent to and in conjunction with each route designator.

The following note appears on Sectionals and TACs covering the conterminous United States.

**MILITARY TRAINING ROUTES (MTRs)**

All IR and VR MTRs are shown, and may extend from the surface upwards. Only the route centerline, direction of flight along the route and the route designator are depicted - route widths and altitudes are not shown.

Since these routes are subject to change every 56 days, and the charts are reissued every 6 months, you are cautioned and advised to contact Flight Service for route dimensions and current status for those routes affecting your flight.

Routes with a change in the alignment of the charted route centerline will be indicated in the Aeronautical Chart Bulletin of the Airport/Facility Directory.

DoD users refer to Area Planning AP/1B Military Training Routes North and South America for current routes.

There are IFR (IR) and VFR (VR) routes as follows: Route identification:

- Routes at or below 1500' AGL (with no segment above 1500') are identified by four-digit numbers; e.g., VR1007, etc. These routes are generally developed for flight under Visual Flight Rules.
- Routes above 1500' AGL (some segments of these routes may be below 1500') are identified by three or fewer digit numbers; e.g., IR21, VR302, etc. These routes are developed for flight under Instrument Flight Rules.

MTRs can vary in width from 4 to 16 miles. Detailed route width information is available in the Flight Information Publication (FLIP) AP/1B (a Department of Defense publication), or through the 56 Day NASR Subscription from the National Flight Data Center (NFDC).

**Special Military Activity** areas are indicated on Sectionals by a boxed note in black type. The note contains radio frequency information for obtaining area activity status.

**SPECIAL MILITARY ACTIVITY**  
CTC MOBILE RADIO  
ON 123.6  
FOR ACTIVITY STATUS

## TERMINAL AREA CHART (TAC) COVERAGE

TAC coverage is shown on appropriate Sectionals by a 1/4" masked line as indicated below.

Within this area pilots should use TACs, which provide greater detail. A note indicating that the area is on the TAC appears near the masked boundary line.

### LOS ANGELES TERMINAL AREA

Pilots are encouraged to use the Los Angeles VFR Terminal Area Chart for flights at or below 10,000'



## INSET COVERAGE


Inset coverage is shown on appropriate Sectionals by a 1/8" masked line as indicated below. A note to this effect appears near the masked boundary line.

If inset chart is on the same chart as outline:

**INDIANAPOLIS INSET**  
See inset chart for additional detail

If inset chart is on a different chart:

**INDIANAPOLIS INSET**  
See inset chart on the St. Louis  
Sectional for additional information





## CHART TABULATIONS

**Airport Tower Communications** are provided in a columnized tabulation for all tower-controlled airports that appear on the respective chart. Airport names are listed alphabetically. If the airport is military, the type of airfield, e.g., AAF, AFB, NAS, is shown after the airfield name. In addition to the airport name, tower operating hours, primary Very High Frequency/Ultra High Frequency (VHF/UHF) local Control Tower (CT), Ground Control (GND CON), and Automatic Terminal Information Service (ATIS) frequencies, when available, will be given. An asterisk (\*) indicates that the part-time tower frequency is remotored to a collocated full-time Flight Service Station (FSS) for use as Airport Advisory Service (AAS) when the tower is closed. Airport Surveillance Radar (ASR) and/or Precision Approach Radar (PAR) procedures are listed when available.

**Approach Control Communications** are provided in a columnized tabulation listing Class B, Class C, Terminal Radar Service Areas (TRSA) and Selected Approach Control Facilities when available. Primary VHF/UHF frequencies are provided for each facility. Sectorization occurs when more than one frequency exists and/or is approach direction dependent. Availability of service hours is also provided.

**Special Use Airspace (SUA):** Prohibited, Restricted and Warning Areas are presented in blue and listed numerically for U.S. and other countries. Restricted, Danger and Advisory Areas outside the U.S. are tabulated separately in blue. A tabulation of Alert Areas (listed numerically) and Military Operations Areas (MOA) (listed alphabetically) appear on the chart in magenta. All are supplemented with altitude, time of use and the controlling agency/contact facility, and its frequency when available. The controlling agency will be shown when the contact facility and frequency data is unavailable.









# VFR AERONAUTICAL CHART SYMBOLS

## AERONAUTICAL INFORMATION

AIRPORTS .....	15
RADIO AIDS TO NAVIGATION .....	17
AIRSPACE INFORMATION .....	19
NAVIGATIONAL AND PROCEDURAL INFORMATION .....	25
CHART LIMITS .....	27

## TOPOGRAPHIC INFORMATION

### CULTURE

RAILROADS .....	28
ROADS .....	28
POPULATED PLACES .....	29
BOUNDARIES .....	29
MISCELLANEOUS CULTURAL FEATURES .....	30

### HYDROGRAPHY

SHORELINES .....	31
LAKES .....	31
RESERVOIRS .....	31
STREAMS .....	31
MISCELLANEOUS HYDROGRAPHIC FEATURES .....	32

### RELIEF

CONTOURS .....	35
ELEVATIONS .....	35
UNRELIABLE RELIEF .....	35
SHADED RELIEF .....	36
AREA RELIEF FEATURES .....	36
MISCELLANEOUS RELIEF FEATURES .....	36

## GENERAL INFORMATION

Symbols shown are for World Aeronautical Charts (WACs), Sectional Aeronautical Charts (Sectionals), Terminal Area Charts (TACs), VFR Flyway Planning Charts and Helicopter Route Charts. When a symbol is different on any VFR chart series, it will be annotated, e.g., “WAC” or “Not shown on WAC.”







## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRPORTS

#### LANDPLANE: CIVIL

Airports having control towers (CT) are shown in blue, all others are shown in magenta.



All recognizable runways, including some which may be closed, are shown for visual identification purposes. Refueling and repair facilities for normal traffic.



Runway patterns will be depicted at airports with at least one hard surfaced runway 1500' or greater in length.



WAC

#### SEAPLANE: CIVIL



WAC

#### LANDPLANE: CIVIL-MILITARY



WAC

#### LANDPLANE: MILITARY

Refueling and repair facilities not indicated.



WAC

### AIRPORTS

#### LANDPLANE: EMERGENCY

No facilities,

or

Complete information is not available.

Add appropriate note as required for hard surfaced runways only: "(CLOSED)"



PUBLIC USE (Soft surfaced runway, or hard surfaced runway less than 1500' in length.) - Limited attendance or no service available

RESTRICTED OR PRIVATE (Soft surfaced runway, or hard surfaced runway less than 1500' in length.) - Use only in emergency, or by specific authorization

UNVERIFIED - A landing area available for public use but warranting more than ordinary precaution due to:  
(1) lack of current information on field conditions, and / or  
(2) available information indicates peculiar operating limitations.

ABANDONED - Depicted for landmark value or to prevent confusion with an adjacent usable landing area. (Normally at least 3000' paved)



WAC

#### SEAPLANE: EMERGENCY

No facilities, or complete information is not available.



WAC

#### HELIPORT (Selected)



WAC

#### ULTRALIGHT FLIGHT PARK (Selected)



Not shown on WAC





## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRPORTS


#### AIRPORT DATA

##### GROUPING

*(Pvt): Non-public use  
having emergency or  
landmark value.*

*“OBJECTIONABLE”:*

*This airport may  
adversely affect  
airspace use.*



- FSS - Flight Service Station on field
- NO SVFR - Airports where fixed wing special visual flight rules operations are prohibited (shown above airport name) F.A.R. 91
- [ ] - Indicates F.A.R. 93 Special Air Traffic Rules and Airport Traffic Patterns
- (NAM) - Location Identifier
- (PNAM) - ICAO Location Indicator
- CT - 118.3 - Control Tower (CT) - primary frequency
  - \* - Star indicates operation part-time. See tower frequencies tabulation for hours of operation
  - C - Follows the Common Traffic Advisory Frequency (CTAF) (Not shown on WAC)
- ATIS 123.8 - Automatic Terminal Information Service
- AFIS 135.2 - Automatic Flight Information Service
- ASOS/AWOS 135.42 - Automated Surface Weather Observing Systems; shown when full-time ATIS is not available. (Not shown on WAC) Some ASOS/AWOS facilities may not be located at airport.
- 897 - Elevation in feet
- L - Lighting in operation Sunset to Sunrise
- \*L - Lighting limitations exist; refer to Airport/Facility Directory.
- 110 - Length of longest runway in hundreds of feet; usable length may be less.
- UNICOM - Aeronautical advisory station ("U" only on WAC)
- RP 23, 34 - Runways with Right Traffic Patterns (public use) (Not shown on WAC)
- RP\* - (See Airport/Facility Directory)
- VFR Advsy 125.0 - VFR Advisory Service shown where ATIS is not available and frequency is other than primary CT frequency.
- WX CAM - Weather Camera (AK)
- AOE - Airport of Entry


When information is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting




## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### RADIO AIDS TO NAVIGATION

#### VHF OMNI-DIRECTIONAL RADIO (VOR) RANGE




#### VOR




#### VORTAC


When an NDB NAVAID shares the same name and Morse Code as the VOR NAVAID the frequency can be collocated inside the same box to conserve space.




#### VOR-DME



#### AIR FORCE STATION (AFS)



#### LONG RANGE RADAR STATION (LRRS)




#### OFF AIRPORT AWOS/ASOS




### RADIO AIDS TO NAVIGATION


#### NON-DIRECTIONAL RADIO BEACON (NDB)



#### NDB-DME



#### NAVAIDS USED TO DEFINE CLASS B AIRSPACE



#### BROADCAST STATIONS (BS)

On request by the proper authority or when a VFR Checkpoint.







## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### RADIO AIDS TO NAVIGATION

#### FLIGHT SERVICE STATION (FSS)

Heavy line box indicates Flight Service Station (FSS).  
Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada -  
121.5, 126.7 and 243.0) are available at many FSSs  
and are not shown above boxes.  
All other frequencies are shown.  
Certain FSSs provide Airport Advisory Service, see A/FD.  
R - Receive only

PONTIAC PTK

No NAVAID of the  
same name as FSS

or

122.1R

IDAHO FALLS  
109.0 Ch 27 IDA

FSS oper 0500-2300  
Boise FSS other times.

NAVAID same name as FSS  
but not an RCO

Transoceanic VHF frequencies are long range  
four digit numbers. These were used during the  
World War II era. They now have become legacy  
frequencies that some Alaska FSSs still maintain  
by doing radio checks with the U.S. Coast Guard.

2866

PONTIAC PTK

#### REMOTE COMMUNICATIONS OUTLET (RCO)

Frequencies above thin line box are remotod to  
NAVAID site. Other FSS frequencies providing  
voice communication may be available as  
determined by altitude and terrain. Consult  
Airport/Facility Directory for complete information.

Thin line box without frequencies and controlling  
FSS name indicates no FSS frequency available.

123.6

OLYMPIA RCO

McCHORD

122.35

ST PAUL  
108.6 STP

MINNEAPOLIS

122.35

HUMPHREY  
275 HPY

MILES CITY

FSS radio providing voice communication

#### ALASKA WEATHER CAMERA

Stand-Alone



ANCHORAGE  
WX CAM

Collocated with Airport - Must be  
within 2 NM to have same name.

WRANGELL (68A)  
00 - 90 122.6  
WX CAM  
AOE



## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### CLASS B AIRSPACE

*Appropriate notes as required may be shown.*


*Only the airspace effective below 18,000 feet MSL are shown.*

*(Mode C see FAR 91.215 /AIM)*

*All mileages are nautical (NM).*

*All radials are magnetic.*

#### LAS VEGAS CLASS B



**FOR FLIGHTS AT AND BELOW 8000' MSL SEE KANSAS CITY VFR TERMINAL AREA CHART**

WAC only

**80** - Ceiling of Class B in hundreds of feet MSL  
**40** - Floor of Class B in hundreds of feet MSL

(Floors extending "upward from above" a certain altitude are preceded by a +. Operations at and below these altitudes are outside of Class B Airspace.)

**CTC LAS VEGAS APP ON 121.1 OR 257.8**

TAC only

### AIRSPACE INFORMATION

#### CLASS C AIRSPACE

*Appropriate notes as required may be shown.*

*(Mode C see FAR 91.215 /AIM)*

#### BURBANK CLASS C

See NOTAMS/Directory for Class C eff hrs



**BOISE CLASS C**

See NOTAMS/Directory for Class C eff hrs



Outer limit only, segments not shown

**FOR FLIGHTS AT OR BELOW 6600 MSL SEE PHOENIX VFR SECTIONAL CHART**

WAC only

**48** - Ceiling of Class C in hundreds of feet MSL  
**30** - Floor of Class C in hundreds of feet MSL


**T** - Ceiling is to but not including floor of Class B  
**SFC** - Surface

**CTC BURBANK APP WITHIN 20 NM ON 124.6 395.9**


Not shown on WAC

#### CLASS D AIRSPACE

See NOTAMS/Directory for Class D eff hrs



See NOTAMS/Directory for Class D/E (sfc) eff hrs



(A minus in front of the figure is used to indicate "from surface to but not including...")

ALTITUDE IN HUNDREDS OF FEET MSL

Not shown on WAC



## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### CLASS E AIRSPACE

The limits of Class E airspace shall be shown by narrow vignettes or by the dashed magenta symbol. Individual units of designated airspace are not necessarily shown; instead, the aggregate lateral and vertical limits shall be defined by the following:

Airspace beginning at the surface (sfc) designated around airports...



See NOTAMs/Directory for Class D/E (sfc) eff hrs



See NOTAMs/Directory for Class E (sfc) eff hrs

Airspace beginning at 700 feet AGL...

See NOTAMs/Directory for 700' Class E eff hrs



Airspace beginning at 700 feet AGL that laterally abuts uncontrolled airspace (Class G)...



**CLASS G**

Airspace beginning at 1200 feet AGL or greater that laterally abuts uncontrolled airspace (Class G)...



Differentiates floors of airspace greater than 700 feet above the surface...



**8000 AGL**

**11,500 MSL**

Not shown on WAC

When the ceiling is less than 18,000 feet MSL, the value, prefixed by the word "ceiling," shall be shown along the limits.

### AIRSPACE INFORMATION

#### OFFSHORE CONTROL AREAS

**ATLANTIC LOW CONTROL AREA**



Class G Airspace

**9500 MSL**

**ATLANTIC LOW CONTROL AREA**



**8000 MSL**

**CONTROL AREA 1148L**

**ATLANTIC LOW CONTROL AREA**



**ATLANTIC LOW CONTROL AREA**

**CONTROL AREA 1148L**

WAC

#### CANADIAN AIRSPACE

Individual units of designated Canadian airspace are not necessarily shown; instead, the aggregate lateral and vertical limits shall be portrayed as closely as possible to the comparable U.S. airspace.

TCA Class B/C/D



TCA Class B/C/D



Outer limit only, segments not shown

WAC

**125** - Ceiling of TCA Class B/C/D in hundreds of feet MSL  
**25** - Floor of TCA Class B/C/D in hundreds of feet MSL



Class D CZ

Class C or D Control Zone

ALTITUDE IN HUNDREDS OF FEET MSL



Class E CZ

Class E Control Zone

Not shown on WAC

Appropriate notes as required may be shown.

AIRSPACE CLASSIFICATION (SEE CANADA FLIGHT SUPPLEMENT) AND OPERATIONAL REQUIREMENTS (DOD USERS, SEE DOD AREA PLANNING AP/1) MAY DIFFER BETWEEN CANADA AND UNITED STATES

NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE





## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION


#### AIRSPACE

##### OUTSIDE OF U.S.

*Other than Canada  
Appropriate notes as  
required may be shown.*

NOTE: DOD USERS, REFER TO CURRENT DOD  
(NGA) FLIGHT INFORMATION PUBLICATIONS FOR  
INFORMATION OUTSIDE OF U.S. AIRSPACE

#### FLIGHT INFORMATION REGIONS (FIR)



#### OCEANIC CONTROL AREAS (OCA)




#### CONTROL AREAS (CTA)



#### LOW ALTITUDE AIRWAYS VOR AND LF/MF (CLASS E AIRSPACE)

*Low altitude Federal  
Airways are indicated  
by centerline.*



*Only the controlled  
airspace effective below  
18,000 feet MSL is  
shown.*



### AIRSPACE INFORMATION

#### MISCELLANEOUS AIR ROUTES

*Combined Federal  
Airway/RNAV "T"  
Routes are identified  
in solid blue type  
adjacent to the solid  
magenta federal airway  
identification. The joint  
route symbol is screened  
magenta.*






## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION


#### SPECIAL USE AIRSPACE

Only the airspace effective below 18,000 feet MSL is shown.

The type of area shall be spelled out in large areas if space permits.



PROHIBITED, RESTRICTED or WARNING AREA



ALERT AREA




MILITARY OPERATIONS AREA (MOA)

#### MILITARY TRAINING ROUTES (MTR)



Not shown on WAC

#### SPECIAL MILITARY ACTIVITY ROUTES (SMAR)



Boxed notes shown adjacent to route.

SPECIAL MILITARY ACTIVITY  
CTC MOBILE RADIO  
ON 123.6  
FOR ACTIVITY STATUS

40 --- Ceiling of SMAR in hundreds of feet MSL  
05 AGL --- Floor of SMAR in hundreds of feet AGL

Not shown on WAC

### AIRSPACE INFORMATION


#### SPECIAL AIR TRAFFIC RULES / AIRPORT PATTERNS (FAR 93)



Appropriate boxed note as required shown adjacent to area.

SPECIAL NOTICE  
Pilots are required to obtain an ATC clearance prior to entering this area.

#### SPACE OPERATIONS AREA (FAR 91.143)



Not shown on WAC

#### MODE C (FAR 91.215)

Appropriate notes as required may be shown.



#### MISCELLANEOUS AIRSPACE AREAS

Parachute Jumping Area with Frequency



Glider Operating Area



Ultralight Activity



Hang Glider Activity



Unmanned Aircraft Activity



Not shown on WAC




## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### SPECIAL CONSERVATION AREAS

*National Park, Wildlife  
Refuge, Primitive and  
Wilderness Areas, etc.*



Not shown on WAC

*NOAA Regulated  
National Marine  
Sanctuary Designated  
Areas*



Flight operations below 1000' AGL  
over the designated areas within the  
Gulf of Farallones National Marine  
Sanctuary violate NOAA regulations  
(see 15 CFR 922).

#### SPECIAL AIRSPACE AREAS

#### SPECIAL FLIGHT RULES AREA (SFRA) RELATING TO NATIONAL SECURITY

*Example: Washington DC*

*Appropriate notes as required  
may be shown.*

*Note: Delimiting line not  
shown when it coincides  
with International  
Boundary, projection lines or  
other linear features.*



Washington DC Metropolitan Area Special Flight Rules  
Area/Flight Restricted Zone restrictions are in effect.  
Special regulations apply to all aircraft operations from the  
surface to but not including Flight Level 180 in the Washington DC  
Metropolitan Area. Pilots should contact a local FSS for NOTAM  
Information prior to flight in the Washington DC Metropolitan Area.


#### FLIGHT RESTRICTED ZONE (FRZ) RELATING TO NATIONAL SECURITY

*Example:  
Washington DC*



### AIRSPACE INFORMATION

#### SPECIAL FLIGHT RULES AREA (SFAR)



**CAUTION**  
Pilots should not attempt flight in the Grand Canyon Special Flight  
Rules area (GCN SFRA) below 18,000 feet using this chart as their  
primary navigational reference. Pilots Intending to fly within the  
Grand Canyon SFRA should refer to the Grand Canyon VFR Aeronautical  
Chart for detailed information. Chart is available from the Federal  
Aviation Administration (phone 1-800-638-8972) or authorized agents.

#### TEMPORARY FLIGHT RESTRICTION (TFR) RELATING TO NATIONAL SECURITY

*Example:*



*Appropriate notes as  
required may be shown.*

**CAUTION**  
P-40 AND R-4009 EXPANDED BY  
TEMPORARY FLIGHT RESTRICTION.  
CONTACT AFSS FOR LATEST STATUS  
AND NOTAMS

Not shown on WAC

#### AIR DEFENSE IDENTIFICATION ZONE (ADIZ)

*Note. Delimiting line not  
shown when it coincides  
with International  
Boundary, projection lines  
or other linear features.*

#### CONTIGUOUS U.S. ADIZ



#### NATIONAL SECURITY AREA

*Appropriate notes as  
required may be shown.*



**NOTICE**  
FOR REASONS OF NATIONAL SECURITY  
PILOTS ARE REQUESTED TO AVOID FLIGHT  
BELOW 1200' MSL IN THIS AREA

Not shown on WAC






## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION


### AIRSPACE INFORMATION

#### HIGH ENERGY RADIATION AREAS

*Appropriate notes as  
required may be shown.*



HAZARDOUS LASER  
TRANSMISSIONS SFC to Infinity  
See Airport Facility/Directory



WAC

#### TERMINAL RADAR SERVICE AREA (TRSA)

##### PALM SPRINGS TRSA



80  
40


- Ceiling of TRSA in hundreds of feet MSL
- Floor of TRSA in hundreds of feet MSL

*Appropriate notes as  
required may be shown.*

SEE TWR FREQ TAB

Not shown on WAC

#### IFR ROUTES



#### VFR TRANSITION ROUTES

*Appropriate notes as  
required may be shown.*

VFR TRANSITION ROUTE  
ATC CLEARANCE REQUIRED  
SEE SHOWBOAT GRAPHIC  
ON SIDE PANEL

Uni-directional



Bi-directional



TAC only




## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### ISOGONIC LINE AND VALUE

*Isogonic lines and values shall be based on the five year epoch magnetic variation model.*



#### LOCAL MAGNETIC NOTES


*Unreliability Notes*

Magnetic disturbance of as much as 78° exists at ground level and 10° or more at 3000 feet above ground level in this vicinity.

#### COMPASS ROSETTE


*Shown only in areas void of VOR roses.*

*Compass rosette will be based on the five year epoch magnetic variation model.*




#### INTERSECTIONS

*Named intersections used as reporting points. Arrows are directed toward facilities which establish intersection.*



#### AIRPORT BEACONS

*Rotating or Flashing*




### NAVIGATIONAL AND PROCEDURAL INFORMATION


#### AERONAUTICAL LIGHTS

*By Request*


Rotating Light with Flashing  
Code Identification Light



Rotating Light with Course  
Lights and Site Number



Flashing Light



#### MARINE LIGHTS

*With Characteristics  
of Light*



R	Red
*W	White
G	Green
B	Blue
SEC	Sector
F	Fixed
Oc	Single Occulting
Oc (2)	Group Occulting
Oc (2+1)	Composite Group Occulting
Iso	Isophase
FI	Flashing
FI (2)	Group Flashing
FI (2+1)	Composite Group Flashing
Q	Quick
IQ	Interrupted Quick
Mo (A)	Morse Code
FFI	Fixed and Flashing
*AI	Alternating
Gp	Group
LFI	Long Flash
Q (3)	Group Quick Flashing
IQ	Interrupted Quick Flashing
VQ	Very Quick Flashing
VQ (3)	Group Very Quick Flashing
IVQ	Interrupted Very Quick Flashing
UQ	Ultra Quick Flashing
IUQ	Interrupted Ultra Quick Flashing

\*Marine Lights are white unless otherwise noted. Alternating lights are red and white unless otherwise noted.




## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### VFR CHECKPOINTS

*Underline indicates proper name of VFR Checkpoint*



#### VFR WAYPOINTS

RNAV



Stand-Alone




Collocated with VFR Checkpoint




Not shown on WAC

#### OBSTRUCTION




#### GROUP OBSTRUCTION



### NAVIGATIONAL AND PROCEDURAL INFORMATION


#### HIGH-INTENSITY OBSTRUCTION LIGHTS

*High-intensity lights may operate part-time or by proximity activation.*



#### WIND TURBINE FARMS

*When highest wind turbine is unverified, UC will be shown after MSL value.*



#### MAXIMUM ELEVATION FIGURE (MEF)

*(see page 7 for explanation).*

**135**

#### WARNING AND CAUTION NOTES

*Used when specific area is not demarcated.*

**WARNING**  
Extensive fleet and air operations being conducted in offshore areas to approximately 100 miles seaward.

**CAUTION:** Be prepared for loss of horizontal reference at low altitude over lake during hazy conditions and at night.






## VFR AERONAUTICAL CHARTS - AERONAUTICAL INFORMATION

### CHART LIMITS

#### OUTLINE ON SECTIONAL OF TERMINAL AREA CHART



#### LOS ANGELES TERMINAL AREA

Pilots are encouraged to use the Los Angeles VFR Terminal Area Chart for flights at or below 10,000'

Not shown on WAC

#### OUTLINE ON SECTIONAL OF INSET CHART



If inset chart is on a different chart:

#### INDIANAPOLIS INSET

See inset chart on the St. Louis Sectional for additional information

If inset chart is on the same chart as outline:

#### INDIANAPOLIS INSET

See inset chart for additional detail

Not shown on WAC




## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION


### CULTURE

#### RAILROADS


*Single Track*




*Double Track*




*More Than Two Tracks*



*Electric*




*Non-operating,  
Abandoned or Under  
Construction*




#### RAILROAD YARDS


*Limiting Track To Scale*




*Location Only*



#### RAILROAD STATIONS



#### RAILROAD SIDINGS AND SHORT SPURS



### CULTURE

#### ROADS

*Dual-Lane Divided  
Highway Category 1*



*Primary  
Category 2*



*Secondary  
Category 2*



#### TRAILS

*Category 3*

*Provides symbolization  
for dismantled railroad  
when combined with label  
"dismantled railroad."*



#### ROAD MARKERS

*Interstate Route No.*



*U.S. Route No.*



*Air Marked  
Identification Label*



#### ROAD NAMES

LINCOLN HIGHWAY

LINCOLN HIGHWAY

WAC

#### ROADS UNDER CONSTRUCTION

under construction






## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION


### CULTURE

#### BRIDGES AND VIADUCTS

*Railroad*



*Road*




#### OVERPASSES AND UNDERPASSES



#### CAUSEWAYS




#### TUNNELS-ROAD AND RAILROAD



#### POPULATED PLACES

*Large Cities Category 1*



*Cities and Large Towns  
Category 2*




*Towns and Villages  
Category 3*



WAC

### CULTURE

#### FERRIES, FERRY SLIPS AND FORDS



#### BOUNDARIES


*International*



*State or Province*



*Convention or  
Mandate Line*



*Date Line*



#### TIME ZONES

PST  
+8 (+7DT) = UTC

MST  
+7 (+6DT) = UTC


Not shown on WAC

#### MINES OR QUARRIES

*Shaft Mines or Quarries*



#### POWER TRANSMISSION AND TELECOMMUNICATION LINES







VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

CULTURE


PIPELINES

pipeline




*Underground*

underground pipeline



DAMS



DAM CARRYING  
ROAD




PASSABLE LOCKS

locks




SMALL LOCKS




WEIRS AND  
JETTIES

jetties




SEAWALLS

seawall




BREAKWATERS

breakwater



PIERS, WHARFS,  
QUAYS, ETC.

piers



CULTURE

MISCELLANEOUS  
CULTURAL FEATURES

- stadium
- fort
- cemetery

OUTDOOR  
THEATER



WELLS

*Other than water*



RACE TRACKS




LOOKOUT TOWERS



LANDMARK AREAS

landfill



TANKS

- water
- oil
- gas


COAST GUARD  
STATION



AERIAL CABLEWAYS,  
CONVEYORS, ETC.



WAC





## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### HYDROGRAPHY


#### OPEN WATER



#### INLAND WATER



#### OPEN/INLAND WATER



#### SHORELINES

*Definite*



*Fluctuating*



*Unsurveyed  
Indefinite*



*Man-made*



#### LAKES

*Label as required*


**Perennial**

*When too numerous to show individual lakes, show representative pattern and descriptive note. Number indicates elevation.*

**Non-Perennial**

*(dry, intermittent, etc.)*


*Illustration includes small perennial lake*



### HYDROGRAPHY

#### RESERVOIRS

*Natural Shorelines*



*Man-made Shorelines*

*Label when necessary for clarity*



*Too small to show to scale*



*Under Construction*



#### STREAMS

*Perennial*



*Non-Perennial*




*Fanned Out  
Alluvial fan*



*Braided*




*Disappearing*




*Seasonally Fluctuating*

*with undefined limits*



*with maximum bank  
limits, prominent  
and constant*





## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### HYDROGRAPHY

*Sand Deposits in and  
along riverbeds*



### WET SAND AREAS

*Within and adjacent  
to desert areas*



### AQUEDUCTS

*Abandoned or Under  
Construction*



*Underground*



*Suspended or Elevated*



*Tunnels*



*Kanats*




*Underground with air vents*



### FLUMES, PENSTOCKS AND SIMILAR FEATURES



*Elevated*



*Underground*



### HYDROGRAPHY

### FALLS

*Double-Line*




*Single-Line*



### RAPIDS

*Double-Line*



*Single-Line*



### CANALS

*ERIE*



*To Scale*



*Abandoned or Under  
Construction*



*Abandoned to Scale*






## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### HYDROGRAPHY

#### SMALL CANALS AND DRAINAGE / IRRIGATION DITCHES


*Perennial*



*Non-Perennial*




*Abandoned or Ancient*



*Numerous*


*Representative pattern and/or  
descriptive note.*



*Numerous*

*numerous canals and ditches*

#### SALT EVAPORATORS AND SALT PANS MAN EXPLOITED



#### SWAMPS, MARSHES AND BOGS



#### HUMMOCKS AND RIDGES



#### MANGROVE AND NIPA



#### PEAT BOGS




### HYDROGRAPHY

#### TUNDRA

tundra

#### CRANBERRY BOGS



cranberry bog

#### RICE PADDIES

*Extensive areas indicated by  
label only.*




#### LAND SUBJECT TO INUNDATION



#### SPRINGS, WELLS AND WATERHOLES




#### GLACIERS




#### GLACIAL MORAINES



#### ICE CLIFFS



#### SNOWFIELDS, ICE FIELDS AND ICE CAPS



#### ICE PEAKS








## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### HYDROGRAPHY

#### FORESHORE FLATS

*Tidal flats exposed at low tide.*



#### ROCKS-ISOLATED

*Bare or Awash*


\*

#### WRECKS


*Exposed*




#### REEFS-ROCKY OR CORAL



#### MISCELLANEOUS UNDERWATER FEATURES NOT OTHERWISE SYMBOLIZED



#### FISH PONDS AND HATCHERIES




### ICE

*Permanent  
Polar Ice*

*Pack Ice*

### HYDROGRAPHY





## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### CONTOURS

*Basic*

#### RELIEF



*Approximate*



*Intermediate*




WAC

*Auxiliary*



WAC

*Depression*  
(Illustration includes  
mound within depression)



*Values*



### SPOT ELEVATIONS


*Position Accurate*



*Position Accurate, Elevation  
Approximate*



*Highest in General Area*



WAC

*Highest on Chart*



#### RELIEF

### MOUNTAIN PASS




### HACHURING



### UNSURVEYED AREAS


*Label appropriately as required*



UNSURVEYED


### UNCONTOURED AREAS

*Label appropriately as required*



RELIEF DATA INCOMPLETE

### DISTORTED SURFACE AREAS



lava

### LAVA FLOWS



lava

### SAND OR GRAVEL AREAS




### SAND RIDGES

*To Scale*



### SAND DUNES

*To Scale*





## VFR AERONAUTICAL CHARTS - TOPOGRAPHIC INFORMATION

### RELIEF

#### SHADED RELIEF




#### ROCK STRATA OUTCROP



rock strata

#### QUARRIES TO SCALE



quarry

#### STRIP MINES, MINE DUMPS AND TAILINGS

*To Scale*




strip mine



mine dump


#### CRATERS



crater

crater

#### ESCARPMENTS, BLUFFS, CLIFFS, DEPRESSIONS, ETC.



#### LEVEES AND ESKERS



levee



# VFR AERONAUTICAL CHART SYMBOLS

## HELICOPTER ROUTE CHARTS

AIRPORTS.....	38
RADIO AIDS TO NAVIGATION.....	38
AIRSPACE INFORMATION.....	39
NAVIGATIONAL AND PROCEDURAL INFORMATION .....	42
CULTURE.....	43
HYDROGRAPHY .....	43
RELIEF.....	43







## HELICOPTER ROUTE CHARTS - AERONAUTICAL INFORMATION

### AIRPORTS

#### LANDPLANE

All recognizable runways, including some which may be closed, are shown for visual identification.



Public



Private



#### HELIPORT

Heliports public and private



Hospital Helipads



Trauma Center



Helipads located at major airports (when requested)



#### SEAPLANE



#### ULTRALIGHT FLIGHT PARK



#### AIRPORT DATA GROUPING

Boxed airport name indicates airport for which a Special Traffic Rule has been established. (Pvt): Non-public use having emergency or landmark value. "OBJECTIONABLE": This airport may adversely affect airspace use.



Rotating Beacon  
In operation  
Sunset to Sunrise

FSS  
NO SVFR  
NAME (NAM) (PNAM)  
CT -119.1 \* 119.8 (HELI)  
ATIS 115.4  
ASOS/AWOS 135.42  
03 L 122.95  
AOE


- FSS - Flight Service Station on field
- NO SVFR - Airspace where fixed wing special visual flight rules operations are prohibited (shown above airport name) F.A.R. 91.
- NAME (NAM) (PNAM) - Indicates F.A.R. 93 Special Air Traffic Rules and Airport Traffic
- (NAM) - Location Identifier
- (PNAM) - ICAO Location Identifier
- CT - 119.1 - Control Tower (CT) - primary frequency
- \* - Star indicates operation part-time. See tower frequencies tabulation for hours of operation.
- ATIS 115.4 - Automatic Terminal Information Service
- ASOS/AWOS 135.42 - Automated Surface Weather Observing Systems (shown when full-time ATIS is not available.) Some ASOS/AWOS facilities may not be located at airports.
- 03 - Elevation in feet
- L - Lighting in operation Sunset to Sunrise
- \*L - Lighting limitations exist, refer to Airport/Facility Directory.
- 122.95 - UNICOM - Aeronautical advisory station
- 119.8 - Follows the Common Traffic Advisory Frequency (CTAF)
- (Unverified) - Unverified Heliport
- AOE - Airport of Entry

When lighting is lacking, the respective character is replaced by a dash. Lighting codes refer to runway edge lights and may not represent the longest runway or full length lighting. Dashes are not shown on heliports or helipads unless additional information follows the elevation (e.g. UNICOM, CTAF).

### RADIO AIDS TO NAVIGATION

#### VHF OMNI-DIRECTIONAL RADIO (VOR) RANGE

VOR-DME  
PROVO  
108.4 Ch 21 PVU



Compass Rose is "reference" oriented to magnetic north.

#### VOR

Operates less than continuous or On-Request Transcribed Weather Broadcast (TWEB)

AMEDEE  
\*109.0 Ch 27 AHC

Underline indicates no voice on this frequency.

#### VORTAC

When an NDB NAVAID shares the same name and Morse Code as the VOR NAVAID the frequency can be collocated inside the same box to conserve space.

NDB Frequency Name ASOS/AWOS  
379 111.0 Ch 47 PTK  
Frequency Channel Identifier

Morse Code

#### VOR-DME

Hazardous Inflight Weather Advisory Service (HIWAS)

SALEM  
114.3 Ch 30 SVM

Crosshatch Indicates Shutdown status

#### NON-DIRECTIONAL RADIO BEACON (NDB)



MONTAGUE  
382 MOG

Underline indicates no voice on this frequency.



#### NDB-DME



GAMBELL  
369 GAM  
DME Ch 92 (114.5)






## HELICOPTER ROUTE CHARTS - AERONAUTICAL INFORMATION

### RADIO AIDS TO NAVIGATION

#### NAVAIDS USED TO DEFINE CLASS B AIRSPACE



#### BROADCAST STATIONS (BS)

On request by the proper  
authority or when a VFR  
Checkpoint.



#### FLIGHT SERVICE STATION (FSS)

Heavy line box indicates Flight Service Station (FSS).  
Frequencies 121.5, 122.2, 243.0 and 255.4 (Canada -  
121.5, 126.7 and 243.0) are available at many FSSs  
and are not shown above boxes.  
All other frequencies are shown.  
Certain FSSs provide Airport Advisory Service, see A/FD.  
R - Receive only

DENVER DEN

No NAVAID of the  
same name as FSS

or

122.1R 123.6  
NORTHWAY  
116.3 Ch 110 ORT


FSS oper 0600-2200  
Rancho Murieta FSS other times.

NAVAID same name as FSS  
but not an RCO

#### REMOTE COMMUNICATIONS OUTLET (RCO)

Frequencies above thin line box are remotized to  
NAVAID site. Other FSS frequencies providing  
voice communication may be available as  
determined by altitude and terrain. Consult  
Airport/Facility Directory for complete information.

Thin line box without frequencies and controlling  
FSS name indicates no FSS frequency available.



FSS radio providing voice communication

### AIRSPACE INFORMATION


#### CLASS B AIRSPACE

Appropriate notes as required  
may be shown. (Mode C see  
FAR 91.215/AIM)

All mileages are nautical  
(NM)

All radials are magnetic.

#### LAS VEGAS CLASS B




(Floors extending "upward from above" a certain  
altitude are preceded by a +. Operations at and below  
these altitudes are outside of Class B Airspace.)

CTC LAS VEGAS APP  
ON 121.1 OR 257.8

#### CLASS C AIRSPACE

Appropriate notes  
as required may be  
shown. (Mode C see  
FAR 91.215/AIM)

#### BURBANK CLASS C



CTC BURBANK APP WITHIN  
20 NM ON 124.6 395.9

#### CLASS D AIRSPACE

See NOTAMS/Directory  
for Class D eff hrs



See NOTAMS/Directory  
for Class D/E (sfc) eff hrs



(A minus in front of the figure is used to  
indicate "from surface to but not including...")

ALTITUDES IN HUNDREDS OF FEET MSL



## HELICOPTER ROUTE CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### CLASS E SURFACE (SFC) AIRSPACE

See NOTAMs/Directory  
for Class E (sfc) eff hrs



#### SPECIAL AIRSPACE AREAS

#### SPECIAL FLIGHT RULES AREA (SFRA) RELATING TO NATIONAL SECURITY

Example: Washington DC

Appropriate notes as  
required may be shown.

Note. Delimiting line not  
shown when it coincides  
with International  
Boundary, projection lines  
or other linear features.



Washington DC Metropolitan Area Special Flight Rules Area/Flight Restricted Zone restrictions are in effect. Special regulations apply to all aircraft operations from the surface to but not including Flight Level 180 in the Washington DC Metropolitan Area. Pilots should contact a local FSS for NOTAM information prior to flight in the Washington DC Metropolitan Area.

#### FLIGHT RESTRICTED ZONE (FRZ) RELATING TO NATIONAL SECURITY

Example:  
Washington DC



#### AIR DEFENSE IDENTIFICATION ZONE (ADIZ)

Note. Delimiting line not  
shown when it coincides  
with International  
Boundary, projection lines  
or other linear features.

#### CONTIGUOUS U.S. ADIZ



### AIRSPACE INFORMATION

#### CANADIAN AIRSPACE

Appropriate notes as  
required may be shown.

TCA Class B/C/D



80  
40

- Ceiling of TCA Class B/C/D in hundreds of feet MSL


- Floor of TCA Class B/C/D in hundreds of feet MSL

Class C or D Control Zone



ALTITUDE IN HUNDREDS OF FEET MSL


Class E Control Zone



AIRSPACE CLASSIFICATION (SEE CANADA FLIGHT SUPPLEMENT) AND OPERATIONAL REQUIREMENTS (DOD USERS, SEE DOD AREA PLANNING AP/1) MAY DIFFER BETWEEN CANADA AND UNITED STATES

NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE

#### HELICOPTER ROUTES



Recommended Route Altitude

500 Maximum  
500 Minimum  
500 Recommended



## HELICOPTER ROUTE CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION


#### SPECIAL USE AIRSPACE

Only the airspace  
effective below 18,000  
feet MSL is shown.

The type of area shall  
be spelled out in large  
areas if space permits.



PROHIBITED, RESTRICTED  
or WARNING AREA



MILITARY OPERATIONS AREA (MOA)  
or ALERT AREA

#### MILITARY TRAINING ROUTES (MTR)



#### SPECIAL AIR TRAFFIC RULES / AIRPORT TRAFFIC AREAS (FAR PART 93)

Appropriate boxed  
notes as required shown  
adjacent to area.



SPECIAL NOTICE  
Pilots are required to  
obtain an ATC clearance  
prior to entering this area.

#### MODE C (FAR 91.215)

Appropriate notes as  
required may be shown.



#### MISCELLANEOUS AIRSPACE AREAS

Parachute Jumping Area  
with Frequency



Glider Operating Area



Ultralight Activity



Hang Glider Activity



Unmanned Aircraft Activity



### AIRSPACE INFORMATION

#### SPECIAL CONSERVATION AREAS

National Park, Wildlife  
Refuge, Primitive and  
Wilderness Areas, etc.



NOAA Regulated  
National Marine  
Sanctuary Designated  
Areas




Flight operations below 1000' AGL  
over the designated areas within the  
Gulf of Farallones National Marine  
Sanctuary violate NOAA regulations  
(see 15 CFR 922).

#### TERMINAL RADAR SERVICE AREA (TRSA)

Appropriate notes as  
required may be shown.

#### PALM SPRINGS TRSA



TRSA  
SURFACE AREA

SEE TWR FREQ TAB

**80** - Ceiling of TRSA in hundreds of feet MSL  
**40** - Floor of TRSA in hundreds of feet MSL








## HELICOPTER ROUTE CHARTS - AERONAUTICAL INFORMATION

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### VFR CHECKPOINTS

*Underline indicates proper name of VFR Checkpoint*



#### VFR WAYPOINTS

*Stand-Alone*




*Collocated with VFR Checkpoint*



*Collocated with VFR Checkpoint & Reporting Point*




#### OBSTRUCTIONS



*High-intensity lights may operate part-time or by proximity activation.*

#### WIND TURBINE FARMS

*When highest wind turbine is unverified, UC will be shown after MSL value.*



### NAVIGATIONAL AND PROCEDURAL INFORMATION


#### MAXIMUM ELEVATION

#### FIGURE (MEF)

*(see page 7 for explanation).*

124

#### NAVIGATION DATA



#### WARNING AND CAUTION NOTES

##### WARNING

Extensive fleet and air operations being conducted in offshore areas to approximately 100 miles seaward.

**CAUTION:** Be prepared for loss of horizontal reference at low altitude over lake during hazy conditions and at night.

#### LOCAL MAGNETIC NOTES

*Unreliability Notes*

Magnetic disturbance of as much as 78° exists at ground level and 10° or more at 3000 feet above ground level in this vicinity.



## HELICOPTER ROUTE CHARTS - TOPOGRAPHIC INFORMATION

### CULTURE

#### RAILROADS

*Single Track*



*Double Track*



#### ROADS

*Dual-Lane:*



*Divided Highways*




*Major Boulevards & Major Streets*



*Primary*




#### BRIDGES



#### POPULATED PLACES

*Built-up Areas*



#### BOUNDARIES

*International*



*State or Province*



#### POWER

#### TRANSMISSION LINES



#### PROMINENT PICTORIALS



TEMPLE

#### LANDMARKS

- |   |                          |
|---|--------------------------|
| ■ Landmark-stadium, factory, school, etc. | ⬆ Lookout Tower          |
| ⚡ Mines or Quarries                       | 🏎 Race Track             |
| 🎪 Outdoor Theater                         | ● Tank-water, oil or gas |

### HYDROGRAPHY


#### SHORELINES



#### MAJOR LAKES AND RIVERS



#### RESERVOIRS



### RELIEF

#### SPOT ELEVATIONS

*Position Accurate*

● 405





# VFR AERONAUTICAL CHART SYMBOLS

## VFR FLYWAY PLANNING CHARTS

AIRPORTS.....	45
RADIO AIDS TO NAVIGATION .....	45
AIRSPACE INFORMATION.....	46
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	48
CULTURE .....	49
HYDROGRAPHY .....	49
RELIEF .....	49





## VFR FLYWAY PLANNING CHARTS - AERONAUTICAL INFORMATION

### AIRPORTS


#### LANDPLANE

No distinction is made between airports with services and those without services. Runways may be exaggerated to clearly portray the pattern. Hard-surfaced runways which are closed but still exist are included in the charted pattern.

*FAR 91 - Fixed wing special VFR operations prohibited.*

*(Pvt): Non-public use having emergency or landmark value. "OBJECTIONABLE": This airport may adversely affect airspace use.*

*ABANDONED - Depicted for landmark value or to prevent confusion with an adjacent usable landing area. Only portrayed beneath or close to the VFR flyway routes or requested by the FAA. (Normally at least 3000' paved).*



### RADIO AIDS TO NAVIGATION

#### VHF OMNI-DIRECTIONAL RADIO RANGE (VOR)

##### VOR



##### VORTAC



##### VOR-DME




#### NON-DIRECTIONAL RADIO BEACON (NDB)



##### NDB-DME



#### NAVAIDS USED TO DEFINE CLASS B AIRSPACE







## VFR FLYWAY PLANNING CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION


#### CLASS B AIRSPACE

*Appropriate notes as required may be shown.*

*(Mode C see FAR 91.215 /AIM)*

*All mileages are nautical (NM).*


*All radials are magnetic.*




#### CLASS C AIRSPACE

*Appropriate notes as required may be shown.*

*(Mode C see FAR 91.215/AIM)*




#### CLASS D AIRSPACE



### AIRSPACE INFORMATION

#### CLASS E SURFACE (SFC) AIRSPACE



#### SPECIAL AIRSPACE AREAS

#### SPECIAL FLIGHT RULES AREA (SFRA) RELATING TO NATIONAL SECURITY

*Example:  
Washington DC*



*Appropriate notes as required may be shown.  
Note. Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.*

Washington DC Metropolitan Area Special Flight Rules Area/Flight Restricted Zone restrictions are in effect. Special regulations apply to all aircraft operations from the surface to but not including Flight Level 180 in the Washington DC Metropolitan Area. Pilots should contact a local FSS for NOTAM information prior to flight in the Washington DC Metropolitan Area.

#### FLIGHT RESTRICTED ZONE (FRZ) RELATING TO NATIONAL SECURITY

*Example:  
Washington DC*






## VFR FLYWAY PLANNING CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### TEMPORARY FLIGHT RESTRICTION (TFR) RELATING TO NATIONAL SECURITY

Example:



Appropriate notes as required may be shown.

**CAUTION**  
P-40 AND R-4009 EXPANDED BY  
TEMPORARY FLIGHT RESTRICTION.  
CONTACT AFSS FOR LATEST STATUS  
AND NOTAMS.


#### AIR DEFENSE IDENTIFICATION ZONE (ADIZ)

Note. Delimiting line not shown when it coincides with International Boundary, projection lines or other linear features.

**CONTIGUOUS U.S. ADIZ**




#### SUGGESTED VFR FLYWAY AND ALTITUDE



#### IFR ROUTES

Arrival

Departure



### AIRSPACE INFORMATION

#### VFR TRANSITION ROUTES

Appropriate notes as required may be shown.

Uni-directional



Bi-directional




VFR TRANSITION ROUTE  
ATC CLEARANCE REQUIRED  
SEE SHOWBOAT GRAPHIC  
ON SIDE PANEL


#### SPECIAL USE AIRSPACE

Only the airspace effective below 18,000 feet MSL is shown.

The type of area shall be spelled out in large areas if space permits.



PROHIBITED, RESTRICTED  
or WARNING AREA



MILITARY OPERATIONS AREA (MOA)  
or ALERT AREA

#### MILITARY TRAINING ROUTES (MTR)



#### SPECIAL AIR TRAFFIC RULES/AIRPORT TRAFFIC AREAS (FAR Part 93)

Appropriate boxed note as required shown adjacent to area.




#### MODE C (FAR 91.215)

Appropriate notes as required may be shown.



#### TERMINAL RADAR SERVICE AREA (TRSA)

**PALM SPRINGS TRSA**



TRSA  
SURFACE AREA

**100** - Ceiling of TRSA in hundreds of feet MSL  
**90** - Floor of TRSA in hundreds of feet MSL



## VFR FLYWAY PLANNING CHARTS - AERONAUTICAL INFORMATION

### AIRSPACE INFORMATION

#### MISCELLANEOUS AIRSPACE AREAS

Parachute Jumping Area



Glider Operating Area



Ultralight Activity



Hang Glider Activity



Unmanned Aircraft Activity



#### SPECIAL CONSERVATION AREAS

NOAA Regulated  
National Marine  
Sanctuary Designated  
Areas




Flight operations below 1000' AGL  
over the designated areas within the  
Gulf of Farallones National Marine  
Sanctuary violate NOAA regulations  
(see 15 CFR 922).

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### VFR CHECKPOINTS

Underline indicates  
proper name of VFR  
Checkpoint



#### VFR WAYPOINTS

Stand-Alone



Collocated with VFR Checkpoint




#### OBSTRUCTIONS


Only obstacles greater than  
999' above ground level  
(AGL) or specified by the  
local ATC Facility shall be  
shown.

AGL heights are not shown.  
High-intensity lights may  
operate part-time or by  
proximity activation.

Under Construction or  
reported and position/  
elevation unverified.



#### NAVIGATIONAL DATA




## VFR FLYWAY PLANNING CHARTS - TOPOGRAPHIC INFORMATION

## CULTURE

## RAILROADS

### Single and Multiple Tracks



## ROADS

Dual-Lane




### Divided Highway Primary



## POPULATED PLACES

*Built-up Areas*



Towns




## BOUNDARIES

International



## POWER

## TRANSMISSION LINES



## PROMINENT PICTORIALS




TEMPLE

## LANDMARKS



## HYDROGRAPHY


## SHORELINES



## MAJOR LAKES AND RIVERS



## RESERVOIRS



## RELIEF

## SPOT ELEVATIONS

### Position Accurate Mountain Peaks








## AIRSPACE CLASSES

AIRSPACE	CLASS A	CLASS B	CLASS C	CLASS D	CLASS E	CLASS G
Entry Requirements	ATC clearance	ATC clearance	ATC clearance for IFR All require radio contact	ATC clearance for IFR All require radio contact	ATC clearance for IFR All IFR require radio contact	None
Minimum Pilot Qualifications	Instrument Rating	Private or Student certification. Local restrictions apply.	Student certificate	Student certificate	Student certificate	Student certificate
Two-Way Radio Communications	Yes	Yes	Yes	Yes	Yes, under IFR flight plan*	Not required*
Special VFR Allowed	No	Yes	Yes	Yes	Yes	N/A
VFR Visibility Minimum	N/A	3 statute miles	3 statute miles	3 statute miles	<b>Below 10,000' MSL</b> 3 statute miles <b>At or above 10,000' MSL</b> 5 statute miles	<b>Below 1200' AGL (regardless of MSL)</b> Day 1 statute mile Night 3 statute miles <b>Above 1200' AGL &amp; below 10,000' MSL</b> Day 1 statute mile Night 3 statute miles <b>Above 1200' AGL &amp; at or above 10,000' MSL</b> 5 statute miles
VFR Minimum Distance From Clouds	N/A	Clear of Clouds	500' below 1000' above 2000' horizontally	500' below 1000' above 2000' horizontally	<b>Below 10,000' MSL</b> 500' below 1000' above 2000' horizontally <b>At or above 10,000' MSL</b> 1000' below 1000' above 1 mile horizontally	<b>Below 1200' AGL (regardless of MSL)</b> Day Clear of Clouds Night 500' below 1000' above 2000' horizontally <b>Above 1200' AGL &amp; below 10,000' MSL</b> Day 500' below 1000' above 2000' horizontally Night 500' below 1000' above 2000' horizontally <b>Above 1200' AGL &amp; at or above 10,000' MSL</b> 1000' below 1000' above 1 mile horizontally
VFR Aircraft Separation	N/A	All	IFR Aircraft	Runway Operations	None	None
Traffic Advisories	Yes	Yes	Yes	Workload permitting	Workload permitting	Workload permitting
Airport Application	N/A	Radar Instrument Approaches Weather Control Tower High Density	Radar Instrument Approaches Weather Control Tower	Instrument Approaches Weather Control Tower	Instrument Approaches Weather	Control Tower
Speed Restrictions	N/A	250 KIAS below 10000' MSL	250 KIAS below 10,000' MSL and 200 KIAS below 2500' AGL within 4nm of the primary airport	250 KIAS below 10,000' MSL and 200 KIAS below 2500' AGL within 4nm of the primary airport	N/A	N/A
Differs from ICAO	No	ICAO does not have speed restriction	ICAO does not have speed restriction ICAO requires ATC clearance	ICAO requires ATC clearance	No	ICAO requires 3 statute miles visibility


\* Unless a temporary tower is present



## AIRSPACE CLASSIFICATION



*U.S. Airspace depiction as shown on Visual Aeronautical Charts*




*Excerpt from Detroit Sectional Chart*



# AeroNav Products

## IFR AERONAUTICAL CHARTS







## IFR AERONAUTICAL CHARTS

## EXPLANATION OF IFR Enroute TERMS AND SYMBOLS

FAA charts are prepared in accordance with specifications of the Interagency Air Cartographic Committee (IACC), and are approved by representatives of the Federal Aviation Administration and the Department of Defense (DoD). Some information on these charts may only apply to military pilots.

The explanations of symbols used on Instrument Flight Rule (IFR) Charts and examples in this section are based primarily on the IFR Enroute Low Altitude Charts. Other IFR products use similar symbols in various colors (see Section 3 of this guide). The chart legends portray aeronautical symbols with a brief description of what each symbol depicts. This section provides more details of the symbols and how they are used on IFR charts.

## AIRPORTS

Active airports with hard-surfaced runways of 3,000' or longer are shown on IFR Enroute Low Altitude Charts - U.S. for the contiguous United States. Airports with hard or soft runways of 3,000' or longer are shown on IFR Enroute Low Altitude Charts - Alaska. Airports with hard-surfaced runways of 5,000' or longer are shown on IFR Enroute High Altitude Charts - U.S. for the contiguous United States. Airports with hard or soft runways of 4000' or longer are shown on IFR Enroute High Altitude Charts - Alaska. Public heliports with an Instrument Approach Procedure (IAP) or requested by the FAA or DoD are depicted on the IFR Enroute Low Altitude Charts. Seaplane bases requested by the FAA or DoD are depicted on the IFR Enroute Low Altitude Charts. Active airports with approved instrument approach procedures are also shown regardless of runway length or composition. On IFR Enroute Low Altitude Charts a tabulation, is provided which identifies airport names, IDs and the panels they are located on. Charted airports are classified according to the following criteria:



**Blue** – Airports with an Instrument Approach Procedure and/or RADAR MINIMA published in the high altitude DoD Flight Information Publications (FLIPs)

**Green** – Airports which have an approved Instrument Approach Procedure and/or RADAR MINIMA published in either the U.S. Terminal Procedures Publications (TPPs) or the DoD FLIPs

**Brown** – Airports without a published Instrument Approach Procedure or RADAR MINIMA


Airports are plotted at their true geographic position, unless the symbol conflicts with a radio aid to navigation (NAVAID) at the same location. In such cases, the airport symbols are displaced. The relationship between the airport and the NAVAID is retained.

Airports are identified by the airport name. In the case of military airports, Air Force Base (AFB), Naval Air Station (NAS), Naval Air Facility (NAF), Marine Corps Air Station (MCAS), Army Air Field (AAF), etc., the abbreviated letters appear as part of the airport name.

Airports marked "Pvt" immediately following the airport name are not for public use, but otherwise meet the criteria for charting as specified above.

Runway length is the length of the longest active runway (including displaced thresholds but excluding overruns) and is shown to the nearest 100 feet using 70 feet as the division point; e.g., a runway of 8,070' is labeled 81.

The following runway compositions (materials) constitute a hard-surfaced runway: asphalt, bitumen, chip seal, concrete, and tar macadam. Runways that are not hard-surfaced have a small letter "s" following the runway length, indicating a soft surface.



1. Airport elevation given in feet above or below mean sea level.
2. Pvt - Private use, not available to general public.
3. A solid line box enclosing the airport name indicates FAR 93 Special Requirements - see Directory/Supplement
4. "NO SVFR" above the airport name indicates FAR 91 fixed-wing special VFR flight is prohibited
5. [C] or [D] following the airport identifier indicates Class C or Class D Airspace.
6. Airport symbol may be offset for enroute navigational aids.
7. Associated city names for public airports are shown above or preceding the airport name. If airport name and city name are the same, only the airport name is shown. The airport identifier in parentheses follows the airport name. City names for military and private airports are not shown.

A **L** symbol following the elevation under the airport name means that runway lights are in operation sunset to sunrise. A **@** symbol indicates there is Pilot Controlled Lighting. A **L\*** symbol means the lighting is part-time or on request, the pilot should consult the Airport/Facility Directory (A/FD) or appropriate Supplement for light operating procedures. The Aeronautical Information Manual (AIM) thoroughly explains the types and uses of airport lighting aids.






## RADIO AIDS TO NAVIGATION (NAVAIDS)

All IFR radio NAVAIDS that have been flight checked and are operational are shown on all IFR Enroute Charts. Very High Frequency/Ultrahigh Frequency (VHF/UHF) NAVAIDS, Very high frequency Omnidirectional Radio range (VORs), Tactical Air Navigation (TACANs) are shown in black, and Low Frequency/Medium Frequency (LF/MF) NAVAIDS, (Compass Locators and Aeronautical or Marine NDBs) are shown in brown.

On IFR Enroute Charts, information about NAVAIDS is boxed as illustrated below. To avoid duplication of data, when two or more NAVAIDS in a general area have the same name, the name is usually printed only once inside an identification box with the frequencies, TACAN channel numbers, identification letters, or Morse Code Identifications of the different NAVAIDS are shown in appropriate colors.

NAVAIDS in a shutdown status have the frequency and channel number crosshatched. Use of the NAVAID status “shutdown” is only used when a facility has been decommissioned but cannot be published as such because of pending airspace actions.



## CONTROLLED AIRSPACE

Controlled airspace consists of those areas where some or all aircraft are subjected to air traffic control within the following airspace classifications of A, B, C, D, & E.

Air Route Traffic Control Centers (ARTCC) are established to provide Air Traffic Control to aircraft operating on IFR flight plans within controlled airspace, particularly during the enroute phase of flight. Boundaries of the ARTCCs are shown in their entirety using the symbol below.



The responsible ARTCC Center names are shown adjacent and parallel to the boundary line.

ARTCC sector frequencies are shown in boxes outlined by the same symbol.



**Class A Airspace** is depicted as open area (white) on the IFR Enroute High Altitude Charts. It consists of airspace from 18,000 Mean Sea Level (MSL) to 60,000 MSL. In aviation terms those altitudes are written as FL 180 to FL 600, (18,000 MSL, is Flight Level (FL) 180, 60,000 MSL, is FL 600.

**Class B Airspace** is depicted as screened blue area with a solid line encompassing the area.

**Class C Airspace** is depicted as screened blue area with a dashed line encompassing the area with a following the airport name.

**Class B and Class C Airspace** consist of controlled airspace extending upward from the surface or a designated floor to specified altitudes, within which all aircraft and pilots are subject to the operating rules and requirements specified in the Federal Aviation Regulations (FAR) 71. Class B and C Airspace are shown in abbreviated forms on IFR Enroute Low Altitude Charts. A general note adjacent to Class B airspace refers the user to the appropriate VFR Terminal Area Chart.

**Class D Airspace** (airports with an operating control tower) are depicted as open area (white) with a following the airport name.

**Class E Airspace** is depicted as open area (white) on the IFR Enroute Low Altitude Charts. It consists of airspace below FL180.

## UNCONTROLLED AIRSPACE


**Class G Airspace** within the United States extends to 14,500' MSL. This uncontrolled airspace is shown as screened brown.

On Area Charts any uncontrolled airspace boundaries are depicted with a .012" brown line and a .060" screen brown band on the uncontrolled side, so as to be seen over the terrain.



## SPECIAL USE AIRSPACE

Special Use Airspace (SUA) confines certain flight activities, restricts entry, or cautions other aircraft operating within specific boundaries. SUA areas are shown in their entirety, even when they overlap, adjoin, or when an area is designated within another area. SUA with altitudes from the surface and above are shown on the IFR Enroute Low Altitude Charts. Similarly, SUA that extends above 18,000' MSL are shown on IFR Enroute High Altitude Charts. On IFR Enroute Altitude Charts tabulations, identify the type of SUA, ID, effective altitudes, times of use, controlling agency and the panel it is located on.



## OTHER AIRSPACE

**FAR 91 Special Air Traffic Rules** are shown with the type NO SVFR above the airport name.

NO SVFR  
AIRPORT NAME

**FAR 93 Special Airspace Traffic Rules** are shown with a solid line box around the airport name, indicating

FAR 93 Special Requirements see Directory/Supplement.

**Mode C Required Airspace** (from the surface to 10,000' MSL) within 30 NM radius of the primary airport(s) for which a Class B airspace is designated, is depicted on IFR Enroute Low Altitude Charts as a blue circle labeled MODE C 30 NM.



Mode C is also required for operations within and above all Class C airspace up to 10,000' MSL, but not depicted. See FAR 91.215 and the AIM.

## INSTRUMENT AIRWAYS

The FAA has established two fixed route systems for air navigation. The VOR and LF/MF system—designated from 1,200' Above Ground Level (AGL) to but not including FL 180—is shown on IFR Enroute Low Altitude Charts, and the Jet Route system—designated from FL 180 to FL 450 inclusive—is shown on IFR Enroute High Altitude Charts.

### VOR LF/MF AIRWAY SYSTEM

#### (IFR LOW ALTITUDE Enroute CHARTS)


In this system VOR airways – airways based on VOR or VORTAC NAVAIDs – are depicted in black and identified by a “V” (Victor) followed by the route number (e.g., “V12”). In Alaska and Canada, some segments of low-altitude airways are based on LF/MF NAVAIDs and are charted in brown instead of black. Routes from a UHF facility to a LF/MF facility change from black to brown at the midpoint.

LF/MF airways – airways based on LF/MF NAVAIDs – are sometimes called “colored airways” because they are identified by color name and number (e.g., “Amber One”, charted as “A1”). In Alaska Green and Red airways are plotted east and west, and Amber and Blue airways are plotted north and south. Regardless of their color identifier, LF/MF airways are shown in brown in the contiguous U.S.

### AIRWAY/ROUTE DATA

On both series of IFR Enroute Charts, airway/route data such as the airway identifications, magnetic courses bearings or radials, mileages, and altitudes (e.g., Minimum Enroute Altitude (MEA), Minimum Obstruction Clearance Altitude (MOCA), Maximum Authorized Altitude (MAA), are shown aligned with the airway. As a rule the airway/route data is charted and in the same color as the airway, with one exception. Charted in blue, Global Navigation Satellite System (GNSS) MEAs, identified with a “G” suffix, have been added to “V” and “colored airways” for aircraft flying those airways using Global Positioning System (GPS) navigation.

Airways/Routes predicated on VOR or VORTAC NAVAIDs are defined by the outbound radial from the NAVAID. Airways/Routes predicated on LF/MF NAVAIDs are defined by the inbound bearing.



Victor Route (with RNAV/GPS MEA shown in blue)




## AREA NAVIGATION (RNAV) "T" ROUTE SYSTEM

The FAA has created new low altitude area navigation (RNAV) "T" routes for the enroute and terminal environments. The RNAV routes will provide more direct routing for IFR aircraft and enhance the safety and efficiency of the National Airspace System. To utilize these routes aircraft are required to be equipped with IFR approved GNSS. In Alaska, TSO-145a and 146a equipment is required.

Low altitude RNAV only routes are identified by the prefix "T", and the prefix "TK" for RNAV helicopter routes followed by a three digit number (T-200 to T-500). Routes are depicted in blue on the IFR Enroute Low Altitude Charts. RNAV route data (route line, identification boxes, mileages, waypoints, waypoint names, magnetic reference courses and MEAs) will also be printed in blue. Magnetic reference courses will be shown originating from a waypoint, fix/reporting point or NAVAID. GNSS MEA for each segment is established to ensure obstacle clearance and communications reception. GNSS MEAs are identified with a "G" suffix.



Joint Victor/RNAV routes are charted as outlined above except as noted. The joint Victor route and the RNAV route identification boxes are shown adjacent to each other. Magnetic reference courses are not shown. MEAs are charted above the appropriate identification box or stacked in pairs, GNSS and Victor. On joint routes, RNAV specific information will be printed in blue.



## OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDE (OROCA)

The Off Route Obstruction Clearance Altitude (OROCA) is depicted on IFR Enroute Low Altitude and Pacific charts and is represented in thousands and hundreds of feet above MSL. OROCAs are shown in every 30 x 30 minute quadrant on Area Charts, every one degree by one degree quadrant for IFR Enroute Low Altitude Charts - U.S. and every two degree by two degree quadrant on IFR Enroute Low Altitude Charts - Alaska. The OROCA represents the highest possible obstruction elevation including both terrain and other vertical obstruction data (towers, trees, etc.) bounded by the ticked lines of latitude/longitude

including data 4 NM outside the quadrant. In this example the OROCA represents 12,500 feet.

OROCA is computed just as the Maximum Elevation Figure (MEF) found on Visual Flight Rule (VFR) Charts except that it provides an additional vertical buffer of 1,000 feet in designated non-mountainous areas and a 2,000 foot vertical buffer in designated mountainous areas within the United States. For areas in Mexico and the Caribbean, located outside the U.S. Air Defense Identification Zone (ADIZ), the OROCA provides obstruction clearance with a 3,000 foot vertical buffer. Evaluating the area around the quadrant provides the chart user the same lateral clearance an airway provides should the line of intended flight follow a ticked line of latitude or longitude. OROCA does not provide for NAVAID signal coverage, communication coverage and would not be consistent with altitudes assigned by Air Traffic Control. OROCAs can be found over all land masses and open water areas containing man-made obstructions (such as oil rigs).

12<sup>5</sup>

## MILITARY TRAINING ROUTES (MTRs)

Military Training Routes (MTRs) are routes established for the conduct of low-altitude, high-speed military flight training (generally below 10,000 feet MSL at airspeeds in excess of 250 knots Indicated Air Speed). These routes are depicted in brown on IFR Enroute Low Altitude Charts, and are not shown on inset charts or on IFR Enroute High Altitude Charts. IFR Enroute Low Altitude Charts depict all IFR Military Training Routes (IRs) and VFR Military Training Routes (VRs), except those VRs that are entirely at or below 1,500 feet AGL.

MTRs are identified by designators (IR-107, VR-134) which are shown in brown on the route centerline. Arrows are shown to indicate the direction of flight along the route. The width of the route determines the width of the line that is plotted on the chart:

Route segments with a width of 5 NM or less, both sides of the centerline, are shown by a .02" line.



Route segments with a width greater than 5 NM, either or both sides of the centerline, are shown by a .035" line.



MTRs for particular chart pairs (ex. L1/2, etc.) are alphabetically, then numerically tabulated. The tabulation includes MTR type and unique identification and altitude range.




## JET ROUTE SYSTEM (HIGH ALTITUDE ENROUTE CHARTS)

Jet routes are based on VOR or VORTAC NAVAIDs, and are depicted in black with a “J” identifier followed by the route number (e.g., “J12”). In Alaska, Russia and Canada some segments of jet routes are based on LF/MF NAVAIDs and are shown in brown instead of black. Routes from a UHF facility to a LF/MF facility change from black to brown at the midpoint.


## AREA NAVIGATION (RNAV) “Q” ROUTE SYSTEM (IFR Enroute HIGH ALTITUDE CHARTS)

The FAA has adopted certain amendments to Title 14, Code of Federal Regulations which paved the way for the development of new area high altitude navigation (RNAV) “Q” routes in the U.S. National Airspace System (NAS). These amendments enable the FAA to take advantage of technological advancements in navigation systems such as the GPS. RNAV “Q” Route MEAs are shown when other than FL 180 MEAs for DME/DME/ Inertial Reference Unit (IRU) RNAV aircraft have a “D” suffix.



RNAV routes and associated data are charted in blue.

“Q” Routes on the IFR Gulf of Mexico charts are shown in black. Magnetic reference courses are shown originating from a waypoint, fix/reporting point, or NAVAID. Joint Jet/RNAV route identification boxes will be located adjacent to each other with the route charted in black. With the exception of Q-Routes in the Gulf of Mexico, GNSS or DME/DME/IRU RNAV are required, unless otherwise indicated. DME/DME/IRU RNAV aircraft should refer to the A/FD or appropriate Supplement for DME information. Altitude values are stacked highest to lowest.



## TERRAIN CONTOURS ON AREA CHARTS

Based on a recommendation of the National Transportation Safety Board, terrain contours have been added to the Enroute Area Charts and are intended to increase pilots’ situational awareness for safe flight over changes in terrain. The following Area Charts portray terrain: Anchorage, Denver, Fairbanks, Juneau, Los Angeles, Nome, Phoenix, San Francisco, Vancouver and Washington.

When terrain rises at least a 1,000 feet above the primary airports’ elevation, terrain is charted using shades of brown with brown contour lines and values. The initial contour will be 1,000 or 2,000 feet above the airports’ elevation. Subsequent intervals will be 2,000 or 3,000 foot increments.

Contours are supplemented with a representative number of spots elevations and are shown in solid black. The highest elevation on an Area Chart is shown with a larger spot and text.

The following boxed note is added to the affected Area Charts:

NOTE: TERRAIN CONTOURS HAVE BEEN ADDED TO THOSE AREA CHARTS WHERE THE TERRAIN ON THE CHART IS 1000 FOOT OR GREATER THAN THE ELEVATION OF THE PRIMARY AIRPORT








# IFR AERONAUTICAL CHART SYMBOLS

## IFR ENROUTE LOW/HIGH ALTITUDE (U.S., PACIFIC AND ALASKA CHARTS)

AIRPORTS.....	59
RADIO AIDS TO NAVIGATION.....	60
AIRSPACE INFORMATION.....	61
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	66
CULTURE.....	67
HYDROGRAPHY.....	67
TOPOGRAPHY.....	67

## OCEANIC ROUTE PLANNING CHARTS, NORTH ATLANTIC, WATRS AND NORTH PACIFIC ROUTE CHARTS

AIRPORTS.....	68
RADIO AIDS TO NAVIGATION.....	68
AIRSPACE INFORMATION.....	69
NAVIGATIONAL AND PROCEDURAL INFORMATION.....	69
CULTURAL BOUNDARIES.....	70
HYDROGRAPHY.....	70







## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### AIRPORTS

#### AIRPORT DATA

##### LOW/HIGH ALTITUDE

Facilities in BLUE or GREEN have an approved Instrument Approach Procedure and/or RADAR MINIMA published in either the FAA Terminal Procedures Publications or the DoD FLIPs. Those in BLUE have an Instrument Approach Procedure and/or RADAR MINIMA published at least in the High Altitude DoD FLIPs. Facilities in BROWN do not have a published Instrument Approach Procedure or RADAR MINIMA.

All IAP Airports are shown on the Low Altitude Charts.

Non-IAP Airports shown on the U.S. Low Altitude Charts have a minimum hard surface runway of 3000'.

Non-IAP Airports shown on the Alaska Low Altitude Charts have a minimum hard or soft surface runway of 3000'.

Airports shown on the U.S. High Altitude Charts have a minimum hard surface runway of 5000'.

Airports shown on the Alaska High Altitude Charts have a minimum hard or soft surface runway of 4000'.

Associated city names for public airports are shown above or preceding the airport name. If airport name and city name are the same, only the airport name is shown. City names for military and private airports are not shown.

The airport identifier in parentheses follows the airport name or Pvt.

Airport symbol may be offset for enroute navigational aids.

Pvt - Private Use

### AIRPORTS

#### CIVIL

##### LOW/ HIGH ALTITUDE



#### CIVIL AND MILITARY

##### LOW/ HIGH ALTITUDE



#### MILITARY

##### LOW/ HIGH ALTITUDE



#### SEAPLANE - CIVIL

##### LOW ALTITUDE




#### HELIPORT

##### LOW ALTITUDE



#### AIRPORT DATA DEPICTION

##### LOW ALTITUDE - U.S. & ALASKA




For complete information consult the Airport/Facility Directory.

1. Airport elevation given in feet above or below mean sea level
2. Pvt - Private use, not available to general public.
3. A solid line box enclosing the airport name indicates FAR 93 Special Requirements- see Directory/Supplement
4. "NO SVFR" above the airport name indicates FAR 91 fixed-wing special VFR flight is prohibited
5. [C] or [D] following the airport identifier indicates Class C or Class D Airspace.
6. Airport symbol may be offset for enroute navigational aids.
7. Associated city names for public airports are shown above or preceding the airport name. If airport name and city name are the same, only the airport name is shown. The airport identifier in parentheses follows the airport name. City names for military and private airports are not shown.
8. Airport Ident ICAO Location Indicator shown outside contiguous U.S.
9. AFIS Alaska only

##### HIGH ALTITUDE - U.S.



##### HIGH ALTITUDE - ALASKA



#### EMERGENCY USE ONLY

##### PACIFIC ONLY








## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### RADIO AIDS TO NAVIGATION

#### VHF OMNIDIRECTIONAL RADIO RANGE (VOR)




**HIGH ONLY**  
(L) Frequency Protection usable range at 18,000' AGL - 40NM  
(T) Frequency Protection usable range at 12,000' AGL - 25NM  
"L" and "T" category NAVAIDS located off Jet Routes are depicted in screen black. NAVAIDS without classification are "H" category.

#### DISTANCE MEASURING EQUIPMENT (DME)

#### TACTICAL AIR NAVIGATION (TACAN)

#### NON-DIRECTIONAL RADIOBEACON (NDB)

#### MARINE RADIOBEACON (RBN)




#### COMPASS LOCATOR BEACON

LOW ALTITUDE




#### ILS LOCALIZER

LOW ALTITUDE




### RADIO AIDS TO NAVIGATION

#### VOR/DME RNAV WAYPOINT DATA



#### NAVIGATION AND COMMUNICATION BOXES

LOW/ HIGH ALTITUDE



Underline indicates No Voice Transmitted on this frequency

TACAN channels are without voice but not underlined



(T) Frequency Protection - usable range 25 NM at 12000' AGL


(Y) TACAN must be placed in "Y" mode to receive distance information

**A** ASOS/AWOS - Automated Surface Observing Station/Automated Weather Observing Station

**H** HIWAS - Hazardous Inflight Weather Advisory Service

**T** TWEB - Transcribed Weather Broadcast (Alaska only)

Automated weather, when available, is broadcast on the associated NAVAID frequency.







## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### RADIO AIDS TO NAVIGATION

#### NAVIGATION AND COMMUNICATION BOXES (CONTINUED)



FSS associated with a NAVAID



Name and identifier of FSS  
not associated with NAVAID

Shadow NAVAID Boxes indicate Flight Service Station (FSS) locations. Frequencies 122.2, 255.4 and emergency 121.5 and 243.0 are available at many FSSs and are not shown. All other frequencies are shown above the box.


Certain FSSs provide Local Airport Advisory (LAA) on 123.6.

Frequencies transmit and receive except those followed by R or T: R - Receive only T - Transmit only

In Canada, shadow boxes indicate FSSs with standard group frequencies of 121.5, 126.7 and 243.0.




Remote Communications Outlet (RCO)  
FSS name and remoted frequency are shown



Thin Line NAVAID Boxes without frequencies and controlling FSS name indicate no FSS frequencies available. Frequencies positioned above thin line boxes are remoted to the NAVAID sites. Other frequencies at the controlling FSS named are available, however, altitude and terrain may determine their reception.

Morse Code is not shown in NAVAID boxes on High Altitude Charts.

- Flight Service Station (FSS), Remote Communications Outlet (RCO) or Automated Weather Observing Station (AWOS/ASOS) not associated with a charted NAVAID or airport.




### AIRSPACE INFORMATION


#### LOW ALTITUDE AIRWAYS

#### LOW/HIGH ALTITUDE


VHF / UHF Data is depicted in Black  
LF / MF Data is depicted in Brown  
RNAV Route data is depicted in Blue



#### HIGH ALTITUDE ROUTES



#### SINGLE DIRECTION ROUTES



#### DIRECTION OF FLIGHT INDICATOR

LOW ALTITUDE - CANADA  
← EVEN

#### SUBSTITUTE ROUTE

LOW/ HIGH ALTITUDE

All relative and supporting  
data shown in brown

See NOTAMs or  
appropriate publication  
for specific information



## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### AIRSPACE INFORMATION

#### UNUSABLE ROUTE

LOW ALTITUDE




HIGH ALTITUDE




#### BY-PASS ROUTE

HIGH ALTITUDE




#### AIRWAY RESTRICTION

LOW ALTITUDE



#### MILITARY TRAINING ROUTES (MTR)

LOW ALTITUDE



#### FIXES/ATC REPORTING REQUIREMENTS

LOW/HIGH ALTITUDE

VHF/UHF

LF/MF



NAMEE  
N00°00.00'  
W00°00.00'



NAMEE  
N00°00.00'  
W00°00.00'

Fix-Compulsory  
Position Report  
Coordinates are shown  
for compulsory, offshore  
and holding fixes

Fix-Non-Compulsory  
Position Report

Off-set arrows indicate facility forming a fix



Airway away from  
VHF/UHF NAVAID  
Airway toward  
LF/MF NAVAID

RNAV



Waypoint-Compulsory  
Position Report

NAMEE  
N00°00.00'  
W00°00.00'

Coordinates are shown  
for off-airway and  
offshore waypoints



Waypoint-Non-Compulsory  
Position Report

NAMEE  
N00°00.00'  
W00°00.00'

Coordinates are shown  
for off-airway and  
offshore waypoints

### AIRSPACE INFORMATION

#### FIXES/ATC REPORTING REQUIREMENTS (CONTINUED)



Reporting Functions at NAVAIDS

VOR-Compulsory  
Position Report

VOR-Non-Compulsory  
Position Report

VOR/DME-Compulsory  
Position Report

VOR/DME-Non-Compulsory  
Position Report

VORTAC-Compulsory  
Position Report

VORTAC-Non-Compulsory  
Position Report

NDB-Compulsory  
Position Report

NDB-Non-Compulsory  
Position Report


NDB/DME-Compulsory  
Position Report

NDB/DME-Non-Compulsory  
Position Report

#### RADIALS AND BEARINGS


*All radials and bearings  
are magnetic*

LOW/ HIGH ALTITUDE



#### FACILITY LOCATORS


LOW/ HIGH ALTITUDE



#### MILEAGES


*All Mileages are  
Nautical (NM)*

LOW /HIGH ALTITUDE



#### DISTANCE MEASURING EQUIPMENT (DME) FIX

LOW/ HIGH ALTITUDE






## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS


### AIRSPACE INFORMATION

#### MINIMUM ENROUTE ALTITUDE (MEA)

All Altitudes Are MSL  
Unless Otherwise Noted




#### MINIMUM ENROUTE ALTITUDE (MEA) GAP




#### MAXIMUM AUTHORIZED ALTITUDE (MAA)

All Altitudes Are MSL  
Unless Otherwise Noted




#### MINIMUM OBSTRUCTION CLEARANCE ALTITUDE (MOCA)


All Altitudes Are MSL  
Unless Otherwise Noted




#### CHANGEOVER POINT



#### ALTITUDE CHANGE



#### MINIMUM CROSSING ALTITUDE (MCA)




#### MINIMUM RECEPTION ALTITUDE (MRA)




### AIRSPACE INFORMATION

#### HOLDING PATTERNS


RNAV Holding Pattern  
Magnetic Reference Bearing  
is determined by the isogonic  
value at the waypoint or fix.




#### AIR DEFENSE IDENTIFICATION ZONE (ADIZ)



#### AIR ROUTE TRAFFIC CONTROL CENTER (ARTCC)




#### AIR TRAFFIC SERVICE IDENTIFICATION DATA




#### ALTIMETER SETTING CHANGE



#### FLIGHT INFORMATION REGIONS (FIR)



#### CONTROL AREAS (CTA)








## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### AIRSPACE INFORMATION

#### UPPER INFORMATION REGIONS (UIR)

#### UPPER CONTROL AREAS (UTA)



#### ADDITIONAL CONTROL AREAS

LOW ALTITUDE  
CONTROL 1234L

HIGH ALTITUDE  
CONTROL 1234H

#### OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDE (OROCA)

LOW ALTITUDE

12<sup>5</sup>


Example: 12,500 feet

OROCA is computed similarly to the Maximum Elevation Figure (MEF) found on Visual charts except that it provides an additional vertical buffer of 1,000 feet in designated non-mountainous areas and a 2,000 foot vertical buffer in designated mountainous areas within the United States.

### AIRSPACE INFORMATION

#### SPECIAL USE AIRSPACE

#### LOW/HIGH ALTITUDE




P-56  
R-123  
W-789  
CYA-101  
CYD-102  
CYR-103  
(MY)D-9

P - Prohibited Area  
R - Restricted Area  
W - Warning area

Canada Only  
CYA - Advisory Area  
CYD - Danger Area  
CYR - Restricted Area

Caribbean Only  
D - Danger Area

In the Caribbean the first two letters represent the country code, i.e. (MY) Bahamas, (MU) Cuba.



EXCLUSION AREA


Line delimits internal separation of same Special Use Area

#### LOW ALTITUDE



A-456  
ABEL MOA

A - Alert Area  
MOA-Military Operation Area



WALL 1  
MOA

WALL 2 MOA

EXCLUSION AREA

Line delimits internal separation of same Special Use Area

SEE AIRSPACE TABULATION ON EACH  
CHART FOR COMPLETE INFORMATION ON :

- AREA IDENTIFICATION
- EFFECTIVE ALTITUDES
- OPERATING TIMES
- CONTROLLING AGENCY A/G CALL PANEL



## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### AIRSPACE INFORMATION

#### CONTROLLED AIRSPACE

##### HIGH ALTITUDE

###### CLASS A AIRSPACE

Open Area (White)

That airspace from 18,000' MSL to and including FL 600, including the airspace overlying the waters within 12 NM of the coast of the contiguous United States and Alaska and designated offshore areas, excluding Santa Barbara Island, Farallon Island, the airspace south of latitude 25°04'00"N, the Alaska peninsula west of longitude 160°00'00"W, and the airspace less than 1,500' AGL.

That airspace from 18,000' MSL to and including FL 450, including Santa Barbara Island, Farallon Island, the Alaska peninsula west of longitude 160°00'00"W, and designated offshore areas.

##### LOW ALTITUDE

###### CLASS B AIRSPACE


Screened Blue with a Solid Blue Outline

That airspace from the surface to 10,000' MSL (unless otherwise designated) surrounding the nation's busiest airports. Each Class B airspace area is individually tailored and consists of a surface area and two or more layers.

###### MODE C AREA

A Solid Blue Outline

That airspace within 30 NM of the primary airports of Class B airspace and within 10 NM of designated airports. Mode-C transponder equipment is required. (see FAR 91.215)



##### LOW ALTITUDE

###### CLASS C AIRSPACE

Screened Blue with a Solid Blue Dashed Outline

That airspace from the surface to 4,000' (unless otherwise designated) above the elevation of selected airports (charted in MSL). The normal radius of the outer limits of Class C airspace is 10 NM. Class C airspace is also indicated by the letter C in a box following the airport name.



##### LOW ALTITUDE

###### CLASS D AIRSPACE

Open Area (White)

That airspace, from the surface to 2,500' (unless otherwise designated) above the airport elevation (charted in MSL), surrounding those airports that have an operational control tower. Class D airspace is indicated by the letter D in a box following the airport name.

### AIRSPACE INFORMATION

#### CONTROLLED AIRSPACE

##### LOW ALTITUDE

###### CLASS E AIRSPACE

Open Area (White)

That controlled airspace below 14,500' MSL which is not Class B, C, or D.

Federal airways from 1,200' AGL to but not including 18,000' MSL (unless otherwise specified).

Other designated control areas below 14,500' MSL.

Not Charted

That airspace from 14,500' MSL to but not including 18,000' MSL, including the airspace overlying the waters within 12 NM of the coast of the contiguous United States and Alaska and designated offshore areas, excluding the Alaska peninsula west of longitude 160°00'00"W and the airspace less than 1,500' AGL.

#### CONTROLLED AIRSPACE


*Canada Only*

##### LOW ALTITUDE

###### CLASS B AIRSPACE

Screened Brown Checkered Area

Controlled airspace above 12,500' MSL



#### UNCONTROLLED AIRSPACE

##### LOW/ HIGH ALTITUDE

###### CLASS G AIRSPACE


Screened Brown Area

Low Altitude

That portion of the airspace below 14,500' MSL that has not been designated as Class B, C, D or E airspace.

High Altitude

That portion of the airspace from 18,000' MSL and above that has not been designated as Class A airspace.



#### CANADIAN AIRSPACE

*Appropriate notes as  
required may be shown.*

##### LOW/HIGH ALTITUDE

AIRSPACE CLASSIFICATION (SEE CANADA FLIGHT SUPPLEMENT) AND OPERATIONAL REQUIREMENTS (DOD USERS SEE DOD AREA PLANNING AP/1) MAY DIFFER BETWEEN CANADA AND THE UNITED STATES

NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE

#### AIRSPACE OUTSIDE OF U.S.

*Other than Canada*

*Appropriate notes as required  
may be shown.*

DOD USERS  
REFER TO CURRENT DOD (NGA) CHARTS  
AND FLIGHT INFORMATION PUBLICATIONS FOR  
INFORMATION OUTSIDE OF U.S. AIRSPACE




## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### ISOGONIC LINE AND VALUE

LOW/ HIGH ALTITUDE

  
Isogonic lines and values shall be based on the five year epoch.

#### TIME ZONE

LOW/ HIGH ALTITUDE

Central Std +6=UTC      Eastern Std +5=UTC

‡ During periods of Daylight Saving Time (DT), effective hours will be one hour earlier than shown. All states observe DT except Arizona and Hawaii.

ALL TIME IS COORDINATED UNIVERSAL TIME (UTC)

#### ENLARGEMENT AREA

LOW/ HIGH ALTITUDE



#### MATCH MARK

LOW/HIGH ALTITUDE



#### NOTES

LOW/ HIGH ALTITUDE

FAA AIR TRAFFIC SERVICE OUTSIDE U.S. AIRSPACE IS PROVIDED IN ACCORDANCE WITH ARTICLE 12 AND ANNEX 11 OF ICAO CONVENTION. ICAO CONVENTION NOT APPLICABLE TO STATE AIRCRAFT BUT COMPLIANCE WITH ICAO STANDARDS AND PRACTICES IS ENCOURAGED.

CAUTION: POSSIBLE DAMAGE AND/OR INTERFERENCE TO AIRBORNE RADIO DUE TO HIGH LEVEL RADIO ENERGY IN THE VICINITY OF R-2206

CAUTION: ACCURACY OF AIR TRAFFIC SERVICES RELATIVE TO HAVANA FIR CANNOT BE CONFIRMED. CONSULT NOTAMS.

North American Datum of 1983 (NAD 83), for charting purposes is considered equivalent to World Geodetic System 1984 (WGS 84).

#### MORSE CODE

LOW/ HIGH ALTITUDE


A - · -	N - · -	1 - - - -
B - · - · -	O - - - -	2 - · - - -
C - - · - · -	P - · - · -	3 - - · - -
D - - · -	Q - - - -	4 - - - · -
E -	R - · -	5 - · - · -
F - · - · -	S - · -	6 - - - · -
G - - -	T -	7 - - - · -
H - · - · -	U - · -	8 - - - - · -
I - · -	V - · - · -	9 - - - - · -
J - - · - -	W - - -	0 - - - - -
K - - · -	X - - - -	
L - · - -	Y - - - -	
M - - -	Z - - - -	

### NAVIGATIONAL AND PROCEDURAL INFORMATION

#### CRUISING ALTITUDES

U.S. only

LOW ALTITUDE




VFR above 3000' AGL unless otherwise authorized by ATC

IFR outside controlled airspace


IFR within controlled airspace as assigned by ATC

All courses are magnetic


HIGH ALTITUDE



VFR or VFR On Top add 500'  
No VFR flights within Class A  
Airspace above 3000' AGL  
unless otherwise authorized by ATC.



No VFR or VFR On Top authorized above FL285 in RVSM airspace.



IFR within controlled airspace as assigned by ATC  
All courses are magnetic



## IFR ENROUTE LOW/HIGH ALTITUDE U.S., PACIFIC AND ALASKA CHARTS

### CULTURE

#### BOUNDARIES

*International*

LOW/ HIGH ALTITUDE

— — — — — Omitted when coincident  
with ARTCC or FIR

*U.S./Russia*

*Maritime Line*

LOW/ HIGH ALTITUDE

RUSSIA  
— + — + —  
UNITED STATES


*Date Line*

LOW/ HIGH ALTITUDE

INTERNATIONAL DATE LINE MONDAY  
SUNDAY

### HYDROGRAPHY


#### SHORELINE



### TOPOGRAPHY

#### TERRAIN

*Area Charts*





## OCEANIC ROUTE PLANNING CHARTS

### AIRPORTS

#### AIRPORT DATA

Airport of Entry (AOE) are shown with four letter ICAO Identifier

#### LANDPLANE-CIVIL

Refueling and repair facilities for normal traffic.



#### LANDPLANE-CIVIL AND MILITARY

Refueling and repair facilities for normal traffic.



#### LANDPLANE-MILITARY

Refueling and repair facilities for normal traffic.



### RADIO AIDS TO NAVIGATION

#### VHF OMNIDIRECTIONAL RADIO RANGE (VOR)



#### DISTANCE MEASURING EQUIPMENT (DME)



#### VOR TACAN (VORTAC)



#### TACTICAL AIR NAVIGATION (TACAN)




#### NON-DIRECTIONAL RADIOBEACON (NDB)



#### DISTANCE MEASURING EQUIPMENT (DME)



#### IDENTIFICATION BOX



### AIRSPACE INFORMATION

#### AIR TRAFFIC SERVICE (ATS) / OCEANIC ROUTES

Note: Mileages are Nautical (NM)

A450	Identification
283	Mileage
UB891	UHF Caribbean Identification
114	Mileage

#### ATS SINGLE DIRECTION ROUTE



#### AERIAL REFUELING TRACKS



#### AIR DEFENSE IDENTIFICATION ZONE (ADIZ)



#### AIR ROUTE TRAFFIC CONTROL CENTER (ARTCC)



#### FLIGHT INFORMATION REGIONS (FIR) AND/OR (CTA)



#### UPPER INFORMATION REGIONS (UIR)



#### UPPER CONTROL AREAS (UTA)



#### OCEANIC CONTROL AREAS (OCA) AND/OR (CTA/FIR)



#### ADDITIONAL OCEANIC CONTROL AREAS

Note: Limits not shown when coincident with Warning Areas.

CONTROL 1485





## OCEANIC ROUTE PLANNING CHARTS

### AIRSPACE INFORMATION

#### BUFFER ZONE



#### NON-FREE FLYING ZONE



#### NORTH ATLANTIC/MINIMUM NAVIGATION PERFORMANCE SPECIFICATIONS (NAT/MNPS)



#### FIXES/ATC REPORTING REQUIREMENTS

*In congested areas select  
fixes have coordinates,  
use, compl/noncompl  
tabulated.*

Name	ARTOP	▲	Compulsory
Latitude & Longitude	N20°52.7' W80°00.0'	△	Non-Compulsory
NAMEE	N00°00.00' W00°00.00'	◆	Waypoint-Compulsory Position Report
			Coordinates are shown for off-airway and offshore waypoints
NAMEE	N00°00.00' W00°00.00'	◆	Waypoint-Non-Compulsory Position Report
			Coordinates are shown for off-airway and offshore waypoints

#### SPECIAL USE AIRSPACE

Warning Area



12 Mile Limit



#### UNCONTROLLED AIRSPACE



### NAVIGATIONAL AND PROCEDURAL INFORMATION


#### MILEAGE CIRCLES

*Note: Mileages are Nautical (NM)*



#### TIME ZONE

*Note: All time is  
Coordinated Universal  
(Standard) Time (UTC)*



#### OVERLAP MARKS


*North Pacific Route  
Chart (NPRC) Only*



#### COMPASS ROSE

*Note: Compass Roses oriented  
to Magnetic North*

*NPRC Only*



#### NOTES

*Warning*

WARNING  
AIRCRAFT INFRINGING UPON  
NON FREE FLYING TERRITORY  
MAY BE FIRED UPON  
WITHOUT WARNING

*NPRC Only*

WARNING  
UNLISTED RADIO EMISSIONS FROM THIS AREA MAY  
CONSTITUTE A NAVIGATION HAZARD OR RESULT IN  
BORDER OVERFLIGHT UNLESS UNUSUAL PRECAUTION  
IS EXERCISED.





OCEANIC ROUTE PLANNING CHARTS

CULTURAL BOUNDARIES

INTERNATIONAL



MARITIME

*NPRC Only*



DATE LINE

*NPRC Only*




HYDROGRAPHY

SHORELINES




IKARIA





# AeroNav Products

## U.S. TERMINAL PROCEDURES PUBLICATION





## U.S. TERMINAL PROCEDURES PUBLICATION

The U.S. Terminal Procedure Publications include the Standard Instrument Approach Procedures (SIAPS), Standard Instrument Departure Procedures (SIDs), Standard Terminal Arrivals (STARs), IFR Takeoff Minimums and (Obstacle) Departure Procedures (ODPs), IFR Alternate Minimums, and Radar Instrument Approach Minimums for use by civil and military aviation.

## EXPLANATION OF TPP TERMS AND SYMBOLS

The discussions and examples in this section will be based primarily on the IFR (Instrument Flight Rule) Terminal Procedures Publication (TPP). Other IFR products use similar symbols in various colors (see Section 2 of this guide). The publication legends list aeronautical symbols with a brief description of what each symbol depicts. This section will provide a more detailed discussion of some of the symbols and how they are used on TPP charts.

FAA charts are prepared in accordance with specifications of the Interagency Air Cartographic Committee (IACC), which are approved by representatives of the Federal Aviation Administration, and the Department of Defense. Some information on these charts may only apply to military pilots.

## PILOT BRIEFING INFORMATION

The pilot briefing information format consists of three horizontal rows of boxed procedure-specific information along the top edge

QUINHAGAK, ALASKA		AL-10363 (FAA)	10266
WAAS CH <b>99311</b> <b>W12A</b>	APP CRS <b>120°</b>	Rwy Idg TDZE Apt Elev <b>4000</b> <b>42</b> <b>42</b>	<b>RNAV (GPS) RWY 12</b> QUINHAGAK (AQH) (PAQH)
Procedure NA at night. Baro-VNAV NA. DME/DME RNP-0.3 NA. Use Platinum altimeter setting.		<b>MISSED APPROACH:</b> Climb to 4500 direct VIVUC and via 087° track to HUBUK and hold, continue climb-in-hold to 4500.	
PLATINUM AWOS-3 <b>118.375</b>		BETHEL RADIO <b>122.1</b>	UNICOM <b>122.8</b> (CTAF)

of the chart. Frequencies and channel, course and elevation values are charted in bold type. The top row contains the primary procedure navigation information, final approach course, landing distance available, touchdown zone, threshold and airport elevations. The middle row contains procedure notes and limitations, icons indicating if nonstandard alternate and/or takeoff minimums apply, approach lighting symbology, and the full text description of the missed approach procedure. The bottom row contains air to ground communication facilities and frequencies in the order in which they are used during an approach with the tower frequency box bolded.

When appears in the Notes section, it signifies the airport has IFR takeoff minimums and/or Departure Procedures published in Section L of the TPP.

**CIVIL USERS NOTE:** FAR 91 prescribes standard takeoff rules and establishes takeoff minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile. These standard minima apply in the absence of any different minima listed in Section L of the TPP.

**ALL USERS:** Airports that have Departure Procedures (DPs) designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR takeoff minimums other than standard, are listed in Section L of the TPP by city. Takeoff Minimums and Departure Procedures apply to all runways unless otherwise

specified. Altitudes, unless otherwise indicated, are minimum altitudes in MSL.

DPs specifically designed for obstacle avoidance may be described in Section L of the TPP in text or published as a graphic procedure. Its name will be listed, and it can be found in either the TPPs (civil) or a separate Departure Procedure volume (military), as appropriate. Users will recognize graphic obstacle DPs by the word “(OBSTACLE)” included in the procedure title; e.g., TETON TWO (OBSTACLE). If not specifically assigned a departure procedure (i.e., ODP, SID, or radar vector) as part of an IFR clearance, an ODP may be required to be flown for obstacle clearance, even though not specifically stated in the IFR clearance. When doing so in this manner, ATC should be informed when the ODP being used contains a specified route to be flown, restrictions before turning, and/or altitude restrictions.

Graphic DPs designed by ATC to standardize traffic flows, ensure aircraft separation and enhance capacity are referred to as “Standard Instrument Departures (SIDs).” SIDs also provide obstacle clearance and are published under the appropriate airport section. ATC clearance must be received prior to flying a SID.

**NOTE:** Graphic Departure Procedures that have been designed primarily to assist Air Traffic Control in providing air traffic separation (as well as providing obstacle clearance) are usually assigned by name in an ATC clearance and are not listed by name in Section L of the TPP.

When appears in the Notes section of the approach chart, it indicates non-standard IFR alternate minimums exist for the airport. When an alternate airport is required, standard IFR alternate minimums apply. Precision approach procedures require a 600’ ceiling and 2 statute miles visibility; nonprecision approaches require an 800’ ceiling and 2 statute miles visibility. This information is found in Section M of the TPP. If appears, alternate minimums are not authorized due to unmonitored facility or absence of weather reporting service. Civil pilots see FAR 91.





The **W** symbol indicates that outages of the WAAS vertical guidance may occur daily at this location due to initial system limitations. WAAS NOTAMs for vertical outages are not provided for this approach. Use LNAV minima for flight planning at these locations, whether as a destination or alternate. For flight operations at these locations, when the WAAS avionics indicate that LNAV/VNAV or LPV service is available, then vertical guidance may be used to complete the approach using the displayed level of service. Should an outage occur during the procedure, reversion to LNAV minima may be required. As the WAAS coverage is expanded, the **W** will be removed.

### PLANVIEW

The data on the planview is drawn to scale, unless one of the following three charting devices are utilized: concentric rings, scale breaks or inset box(es). In many cases, obstructions close to the airport can be depicted within the parameters of the airport sketch.

### Terrain Depiction

Terrain will be depicted with contour lines in shades of brown, in the planview portion of all IAPs at airports that meet the following criteria:

- If the terrain within the planview exceeds 4,000 feet above the airport elevation, or
- If the terrain within a 6.0 nautical mile radius of the Airport Reference Point (ARP) rises to at least 2,000 feet above the airport elevation.

Approximately 1200 airports throughout the US currently meet the above criteria.

### MISSED APPROACH ICONS

Boxed MAP icons, placed in the profile section, are intended to provide quick at-a-glance intuitive guidance to the pilot to supplement, not replace, the textual missed approach instructions in the briefing strip. These step-by-step instructional graphics depict direction of turn, next heading/course/bearing/track, next altitude, etc. to give the pilot the “up and out” initial steps of the missed approach.



### IFR LANDING MINIMA

The United States Standard for Terminal Instrument Procedures (TERPS) is the approved criteria for formulating instrument approach procedures. Landing minima are established for six aircraft categories (ABCDE and COPTER). In the absence of COPTER MINIMA, helicopters may use the CAT A minimums of other procedures.








### CIRCLING APPROACH OBSTACLE PROTECTED AIRSPACE


The circling MDA provides vertical clearance from obstacles when conducting a circle-to-land maneuver within the obstacle protected area. Circling approach obstacle protected areas extend laterally and longitudinally from the centerlines and ends of all runways at an airport by the distances shown in the following tables. The areas are technically defined by the tangential connection of arcs drawn at the radius distance shown from each runway end.

#### STANDARD CIRCLING APPROACH MANEUVERING RADIUS

Circling approach protected areas developed prior to late 2012 used the radius distances shown in the following table, expressed in nautical miles (NM), dependent on aircraft approach category. The approaches using standard circling approach areas can be identified by the absence of the  symbol on the circling line of minima.

Circling MDA in feet MSL	Approach Category and Circling Radius (NM)				
	CAT A	CAT B	CAT C	CAT D	CAT E
All Altitudes	1.3	1.5	1.7	2.3	4.5

#### EXPANDED CIRCLING APPROACH MANEUVERING AIRSPACE RADIUS

Circling approach protected areas developed after late 2012 use the radius distance shown in the following table, expressed in nautical miles (NM), dependent on aircraft approach category, and the altitude of the circling MDA, which accounts for true airspeed increase with altitude. The approaches using expanded circling approach areas can be identified by the presence of the  symbol on the circling line of minima.

Circling MDA in feet MSL	Approach Category and Circling Radius (NM)				
	CAT A	CAT B	CAT C	CAT D	CAT E
1000 or less	1.3	1.7	2.7	3.6	4.5
1001-3000	1.3	1.8	2.8	3.7	4.6
3001-5000	1.3	1.8	2.9	3.8	4.8
5001-7000	1.3	1.9	3.0	4.0	5.0
7001-9000	1.4	2.0	3.2	4.2	5.3
9001 and above	1.4	2.1	3.3	4.4	5.5

### TERMINAL ARRIVAL AREAS (TAAs)

The objective of the Terminal Arrival Area (TAA) is to provide a seamless transition from the enroute structure to the terminal environment for arriving aircraft equipped with Flight Management System (FMS) and/or Global Positioning System (GPS) navigational equipment. The underlying instrument approach procedure is an area navigation (RNAV) procedure. The TAA contains within it a “T” structure that normally provides for a No Procedure Turn (NoPT) for aircraft using the approach. The TAA provides the pilot and air traffic controller with a very efficient method for routing traffic into the terminal environment with little required air traffic control interface, and with minimum altitudes depicted that provide standard obstacle clearance compatible with the instrument procedure associated with it. The TAA will not be found on all RNAV procedures, particularly in areas of heavy concentration of air traffic. When the TAA is published, it replaces the MSA for that approach procedure. TAAs may appear on GPS and RNAV IAP charts.

NOTE: Additional information for the TAAs can be found in the Aeronautical Information Manual (AIM) Para 5-4-5-d.





# Instrument Approach Chart Format

Pilot  
Briefing  
Information

JACKSONVILLE, FLORIDA

AL-5570 (FAA)

13010

WAAS CH <b>70626</b> <b>W14A</b>	APP CRS <b>136°</b>	Rwy Idg THRE Apt Elev	<b>7701</b> <b>27</b> <b>29</b>
--	------------------------	-----------------------------	---------------------------------------

**RNAV (GPS) Z RWY 14**  
JACKSONVILLE INTL (JAX)


<p>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). For inoperative MALSR, increase LNAV/VNAV all Cnts visibility to 1½ miles and increase LNAV Cnts A/B to 1 mile. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM not authorized.</p>	MALSR 	MISSED APPROACH: Climb to 500 then climbing left turn to 2000 direct YEJWO and hold.
--	-----------	---

ATIS <b>125.85</b>	JACKSONVILLE APP CON <b>119.0 335.6</b>	JACKSONVILLE TOWER <b>118.3 317.7</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>119.5 290.275</b>
-----------------------	--	--	-------------------------------	----------------------------------

Terminal  
Arrival  
Areas  
(TAAs)

Missed  
Approach  
Icons

RNAV  
Minima



ELEV 29		THRE 27	
4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.02/TCH 70).	
OSBAJ		WOLQU	
2000		1700	
GS 3.00°		1.2 NM to RW14	
TCH 54		* LNAV only	
6.7 NM		3.9 NM	
1.2		1.2	
CATEGORY	A	B	C
LPV DA	227-½	200 (200-½)	
LNAV/VNAV DA	363-¾	336 (400-¾)	
LNAV MDA	480-¾	453 (500-¾)	480-⅞ 453 (500-⅞)
CIRCLING	520-1	491 (500-1)	520-1½ 491 (500-1½) 640-2 611 (700-2)

JACKSONVILLE, FLORIDA

Amdt 2 10JAN13

30°30'N-81°41'W

JACKSONVILLE INTL (JAX)

**RNAV (GPS) Z RWY 14**



# U.S. TERMINAL PROCEDURES PUBLICATION SYMBOLS

## AERONAUTICAL INFORMATION

STANDARD TERMINAL ARRIVAL (STAR) CHARTS .....	77
DEPARTURE PROCEDURE (DP) CHARTS .....	77
APPROACH LIGHTING SYSTEM .....	78
AIRPORT DIAGRAM/SKETCH .....	81
INSTRUMENT APPROACH PROCEDURES PLANVIEW .....	83
INSTRUMENT APPROACH PROCEDURES PROFILE VIEW .....	85

## GENERAL INFORMATION

Symbols shown are for the Terminal Procedures Publication (TPP) which includes Standard Terminal Arrival Routes (STARs), Departure Procedures (DPs), Instrument Approach Procedures (IAP) and Airport Diagrams.







## U.S. TERMINAL PROCEDURES PUBLICATION

### LEGEND


#### STANDARD TERMINAL ARRIVAL (STAR) CHARTS DEPARTURE PROCEDURE (DP) CHARTS

Applies to both STAR and DP Charts unless otherwise noted.


##### RADIO AIDS TO NAVIGATION



##### FIXES/ATC REPORTING REQUIREMENTS




##### ROUTES




##### SPECIAL USE AIRSPACE



##### ALTITUDES




##### ATC CROSSING ALTITUDES (DP)




##### INDICATED AIRSPEED



##### AIRPORTS




##### MISCELLANEOUS





## U.S. TERMINAL PROCEDURES PUBLICATION

## APPROACH LIGHTING SYSTEM

## RUNWAY TOUCHDOWN ZONE AND CENTERLINE LIGHTING SYSTEMS




## APPROACH LIGHTING SYSTEM


**ALSF-2****ALSF-1**

## APPROACH LIGHTING SYSTEM


## SHORT APPROACH LIGHTING SYSTEM




**SIMPLIFIED SHORT  
APPROACH LIGHTING  
SYSTEM WITH  
RUNWAY ALIGNMENT  
INDICATOR LIGHTS**  
*SSALR*



**MEDIUM INTENSITY  
(MALS AND MALSF)  
OR SIMPLIFIED SHORT  
(SSALS AND SSALF)  
APPROACH LIGHTING  
SYSTEMS**



**MEDIUM INTENSITY  
APPROACH LIGHTING  
SYSTEM WITH  
RUNWAY ALIGNMENT  
INDICATOR LIGHTS**  
*MALSR*








## U.S. TERMINAL PROCEDURES PUBLICATION

### APPROACH LIGHTING SYSTEM

#### OMNIDIRECTIONAL APPROACH LIGHTING SYSTEM

*ODALS*



#### VISUAL APPROACH SLOPE INDICATOR


*VASI*



#### VASI

VISUAL APPROACH SLOPE INDICATOR  
WITH STANDARD THRESHOLD CLEARANCE  
PROVIDED.

ALL LIGHTS WHITE — TOO HIGH  
FAR LIGHTS RED  
NEAR LIGHTS WHITE — ON GLIDE SLOPE  
ALL LIGHTS RED — TOO LOW




### APPROACH LIGHTING SYSTEM

#### "T"-VISUAL APPROACH SLOPE INDICATOR


*"T"-VASI*



#### "T"-VASI



"T" ON BOTH SIDES OF RWY  
ALL LIGHTS VARIABLE WHITE.  
CORRECT APPROACH SLOPE-  
ONLY CROSS BAR VISIBLE.  
UPRIGHT "T"- FLY UP.  
INVERTED "T"- FLY DOWN.  
RED "T"- GROSS  
UNDERSHOOT.




#### VISUAL APPROACH SLOPE INDICATOR

*VASI*

#### VASI



VISUAL APPROACH SLOPE INDICATOR  
WITH A THRESHOLD CROSSING HEIGHT TO  
ACCOMMODATE LONG BODIED OR JUMBO  
AIRCRAFT.




#### PRECISION APPROACH PATH INDICATOR

*PAPI*

#### PAPI



Legend: □ White ■ Red






## U.S. TERMINAL PROCEDURES PUBLICATION

### APPROACH LIGHTING SYSTEM

#### PULSATING VISUAL APPROACH SLOPE INDICATOR


*PVASI*



**CAUTION:** When viewing the pulsating visual approach slope indicators in the pulsating white or pulsating red sectors, it is possible to mistake this lighting aid for another aircraft or a ground vehicle. Pilots should exercise caution when using this type of system.

#### TRI-COLOR VISUAL APPROACH SLOPE INDICATOR


*TRCV*



**CAUTION:** When the aircraft descends from green to red, the pilot may see a dark amber color during the transition from green to red.

#### ALIGNMENT OF ELEMENT SYSTEMS

*APAP*




Painted panels which may be lighted at night.  
To use the system the pilot positions the aircraft  
so the elements are in alignment.




## U.S. TERMINAL PROCEDURES PUBLICATION

### AIRPORT DIAGRAM/SKETCH

#### ARRESTING GEAR

 uni-directional

 bi-directional

 Jet Barrier

 Arresting System

ARRESTING GEAR: Specific arresting gear systems; e.g., BAK12, MA-1A etc., shown on airport diagrams, not applicable to Civil Pilots. Military Pilots refer to appropriate DOD publications.

#### REFERENCE FEATURES

■ Buildings

 24-Hour Self-Serve Fuel ##.

● Tanks

△ Obstruction

☆ Airport Beacon

✕ Runway Radar Reflectors

 Hot Spot

TWR  Control Tower #

# When Control Tower and Rotating Beacon are co-located, Beacon symbol will be used and further identified as TWR.

## A fuel symbol is shown to indicate 24-hour self-serve fuel available, see appropriate A/FD, Alaska or Pacific Supplement for information.

#### Helicopter Alighting Areas



Negative Symbols used to identify  
Copter Procedures landing point



Runway Threshold elevation...THRE 123

Runway TDZ elevation.....TDZE 123


— 0.3% DOWN

0.8% UP — Runway Slope

(shown when runway slope equals or exceeds 0.3%)


NOTE:

Runway Slope measured to midpoint on runways 8000 feet or longer.

A  symbol is shown to indicate runway declared distance information available, see appropriate A/FD, Alaska or Pacific Supplement for distance information.

### AIRPORT DIAGRAM/SKETCH

#### NOTES

 U.S. Navy Optical Landing System (OLS) "OLS" location is shown because of its height of approximately 7 feet and proximity to edge of runway may create an obstruction for some types of aircraft.

Approach light symbols are shown in the Flight Information Handbook.

Airport diagram scales are variable.

True/magnetic North orientation may vary from diagram to diagram

Coordinate values are shown in 1 or ½ minute increments. They are further broken down into 6 second ticks, within each 1 minute increments.

Positional accuracy within ±600 feet unless otherwise noted on the chart.

NOTE:

All new and revised airport diagrams are shown referenced to the World Geodetic System (WGS) (noted on appropriate diagram), and may not be compatible with local coordinates published in FLIP. (Foreign Only)













## U.S. TERMINAL PROCEDURES PUBLICATION

### AIRPORT DIAGRAM/SKETCH


#### RUNWAYS

	Hard Surface		Closed Runway
	Other than hard surface		Closed Taxiway
	Stopways, Taxiways, Parking Areas		Under Construction
	Displaced Threshold		Metal Surface

Runway length depicted is the physical length of the runway (end-to-end, including displaced thresholds if any) but excluding areas designated as stopways.

Runway Weight Bearing Capacity/or PCN Pavement Classification Number is shown as a codified expression.

Refer to the appropriate Supplement/Directory for applicable codes e.g.,  
RWY 14-32 PCN 80 F/D/X/U S-75, D-185, 2S-175, 2D-325



#### SCOPE


Airport diagrams are specifically designed to assist in the movement of ground traffic at locations with complex runway/taxiway configurations. Airport diagrams are not intended to be used for approach and landing or departure operations. For revisions to Airport Diagrams: Consult FAA Order 7910.4.




## U.S. TERMINAL PROCEDURES PUBLICATION

### INSTRUMENT APPROACH PROCEDURES PLANVIEW

#### TERMINAL ROUTES



#### HOLDING PATTERNS



Limits will only be specified when they deviate from the standard.  
Holding pattern with max. restricted airspeed: (175K) applies to all altitudes. (210K) applies to altitudes above 6000' to and including 14000'.  
DME fixes may be shown.  
Arrival Holding Pattern altitude restrictions will be indicated when they deviate from the adjacent leg.

#### FIXES/ATC REPORTING REQUIREMENTS

##### Reporting Point

▲ Name (Compulsory)

△ Name (Non-Compulsory)



WAYPOINT  
(Compulsory)



WAYPOINT  
(Non-Compulsory)

##### FLYOVER POINT



##### Intersection




##### MAP WP (Flyover)



##### Computer Navigation Fix (CNF)

x (NAME) ("x" omitted when it conflicts with runway pattern)




R-198 Radial line and value

LR-198 Lead Radial

LB-198 Lead Bearing

### INSTRUMENT APPROACH PROCEDURES PLANVIEW

#### RADIO AIDS TO NAVIGATIONS



LOM/LMM (Compass locator at Outer/Middle Marker)



#### Marker Beacon




#### Localizer

(LOC/LDA)

Course





SDF Course




#### LOC/DME

#### LOC/LDA/SDF/MLS Transmitter

(shown when installation is offset from its normal position off the end of the runway.)



#### MINIMUM SAFE ALTITUDE








## U.S. TERMINAL PROCEDURES PUBLICATION


### INSTRUMENT APPROACH PROCEDURES PLANVIEW

#### TERMINAL ARRIVAL AREAS



Minimum MSL altitudes are charted within each of these defined areas/subdivisions that provide at least 1,000 feet of obstacle clearance, or more as necessary in mountainous areas.

#### SPECIAL USE AIRSPACE



R-Restricted  
P-Prohibited  
MOA-Military Operations Area  
W-Warning  
A-Alert

#### OBSTACLES


- Spot Elevation
- Highest Spot Elevation
- △ Obstacle
- △ Highest Obstacle
- ± Doubtful accuracy

#### ALTITUDES


5500 Mandatory Altitude (Cross at)  
2300 Minimum Altitude (Cross at or)  
4800 Maximum Altitude (Cross at or)  
2200 Recommended Altitude  
5000  
3000 Mandatory Block Altitude

### INSTRUMENT APPROACH PROCEDURES PLANVIEW


#### MISCELLANEOUS



**Miscellaneous Symbols**  
Miscellaneous Symbols are occasionally used as a reference mark to connect information from two different areas on a chart.



#### AIRPORTS



#### INDICATED AIRSPEED

**INDICATED AIRSPEED**  
175K 120K 250K 180K  
Mandatory Minimum Maximum Recommended  
Airspeed Airspeed Airspeed Airspeed







[aeronav.faa.gov](https://aeronav.faa.gov)



[aeronav.faa.gov](https://aeronav.faa.gov)